



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'wmemset.3p' command

\$ man wmemset.3p

WMEMSET(3P) POSIX Programmer's Manual WMEMSET(3P)

PROLOG

This manual page is part of the POSIX Programmer's Manual. The Linux implementation of this interface may differ (consult the corresponding Linux manual page for details of Linux behavior), or the interface may not be implemented on Linux.

NAME

wmemset ? set wide characters in memory

SYNOPSIS

```
#include <wchar.h>

wchar_t *wmemset(wchar_t *ws, wchar_t wc, size_t n);
```

DESCRIPTION

The functionality described on this reference page is aligned with the ISO C standard. Any conflict between the requirements described here and the ISO C standard is unintentional. This volume of POSIX.1?2017 defers to the ISO C standard.

The `wmemset()` function shall copy the value of `wc` into each of the first `n` wide characters of the object pointed to by `ws`. This function shall not be affected by locale and all `wchar_t` values shall be treated identically. The null wide character and `wchar_t` values not corresponding to valid characters shall not be treated specially.

If `n` is zero, the application shall ensure that `ws` is a valid pointer, and the function shall copy zero wide characters.

RETURN VALUE

The `wmemset()` functions shall return the value of `ws`.

ERRORS

No errors are defined.

The following sections are informative.

EXAMPLES

None.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

`wmemchr()`, `wmemcmp()`, `wmemcpy()`, `wmemmove()`

The Base Definitions volume of POSIX.1-2017, `<wchar.h>`

COPYRIGHT

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1-2017, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 7, 2018 Edition, Copyright (C) 2018 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html>.

Any typographical or formatting errors that appear in this page are most likely to have been introduced during the conversion of the source files to man page format. To report such errors, see https://www.kernel.org/doc/man-pages/reporting_bugs.html.