



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'xzcmp.1' command

\$ man xzcmp.1

XZDIFF(1)

XZ Utils

XZDIFF(1)

NAME

xzcmp, xzdiff, lzcmp, lzdiff - compare compressed files

SYNOPSIS

xzcmp [cmp_options] file1 [file2]

xzdiff [diff_options] file1 [file2]

lzcmp [cmp_options] file1 [file2]

lzdif [diff_options] file1 [file2]

DESCRIPTION

xzcmp and xzdiff invoke cmp(1) or diff(1) on files compressed with xz(1), lzma(1), gzip(1), bzip2(1), or lzop(1). All options specified are passed directly to cmp(1) or diff(1). If only one file is specified, then the files compared are file1 (which must have a suffix of a supported compression format) and file1 from which the compression format suffix has been stripped. If two files are specified, then they are uncompressed if necessary and fed to cmp(1) or diff(1). The exit status from cmp(1) or diff(1) is preserved.

The names `Izcmp` and `Izdiff` are provided for backward compatibility with

LZMA Utils.

SEE ALSO

`cmp(1)`, `diff(1)`, `xz(1)`, `gzip(1)`, `bzip2(1)`, `lzop(1)`, `zdiff(1)`

BUGS

Messages from the `cmp(1)` or `diff(1)` programs refer to temporary file?

names instead of those specified.

Tukaani

2011-03-19

XZDIFF(1)