



Rocky Enterprise Linux 9.2 Manual Pages on command 'aa-remove-unknown.8'

C:\>man aa-remove-unknown.8

AA-REMOVE-UNKNOWN(8) AppArmor AA-REMOVE-UNKNOWN(8)

NAME

aa-remove-unknown - remove unknown AppArmor profiles

SYNOPSIS

aa-remove-unknown [option]

DESCRIPTION

aa-remove-unknown will inventory all profiles in /etc/apparmor.d/, compare that list to the profiles currently loaded into the kernel, and then remove all of the loaded profiles that were not found in /etc/apparmor.d/. It will also report the name of each profile that it removes on standard out.

OPTIONS

-h, --help

displays a short usage statement.

-n dry run; only prints the names of profiles that would be removed

EXAMPLES

\$ sudo ./aa-remove-unknown -n

Would remove 'test//null-/usr/bin/whoami'

Would remove 'test'

```
$ sudo ./aa-remove-unknown
```

Removing 'test//null-/usr/bin/whoami'

Removing 'test'

BUGS

None. Please report any you find to Launchpad at
<<https://bugs.launchpad.net/apparmor/+filebug>>.

SEE ALSO

apparmor(7)

AppArmor 2.13.3

2020-05-19

AA-REMOVE-UNKNOWN(8)