



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ASN1_item_d2i_bio_ex.3ossl'

\$ man ASN1_item_d2i_bio_ex.3ossl

ASN1_ITEM_D2I_BIO(3ossl) OpenSSL ASN1_ITEM_D2I_BIO(3ossl)

NAME

ASN1_item_d2i_ex, ASN1_item_d2i, ASN1_item_d2i_bio_ex,
ASN1_item_d2i_bio, ASN1_item_d2i_fp_ex, ASN1_item_d2i_fp,
ASN1_item_i2d_mem_bio - decode and encode DER-encoded ASN.1 structures

SYNOPSIS

```
#include <openssl/asn1.h>
```

```
ASN1_VALUE *ASN1_item_d2i_ex(ASN1_VALUE **pval, const unsigned char **in,  
                             long len, const ASN1_ITEM *it,  
                             OSSL_LIB_CTX *libctx, const char *propq);  
ASN1_VALUE *ASN1_item_d2i(ASN1_VALUE **pval, const unsigned char **in,  
                           long len, const ASN1_ITEM *it);
```

```
void *ASN1_item_d2i_bio_ex(const ASN1_ITEM *it, BIO *in, void *x,  
                           OSSL_LIB_CTX *libctx, const char *propq);
```

```
void *ASN1_item_d2i_bio(const ASN1_ITEM *it, BIO *in, void *x);
```

```
void *ASN1_item_d2i_fp_ex(const ASN1_ITEM *it, FILE *in, void *x,  
                          OSSL_LIB_CTX *libctx, const char *propq);
```

```
void *ASN1_item_d2i_fp(const ASN1_ITEM *it, FILE *in, void *x);
```

```
BIO *ASN1_item_i2d_mem_bio(const ASN1_ITEM *it, const ASN1_VALUE *val);
```

DESCRIPTION

`ASN1_item_d2i_ex()` decodes the contents of the data stored in `*in` of length `len` which must be a DER-encoded ASN.1 structure, using the ASN.1 template `it`. It places the result in `*pval` unless `pval` is NULL. If `*pval` is non-NULL on entry then the `ASN1_VALUE` present there will be reused. Otherwise a new `ASN1_VALUE` will be allocated. If any algorithm fetches are required during the process then they will use the `OSSL_LIB_CTX` provided in the `libctx` parameter and the property query string in `propq`. See "ALGORITHM FETCHING" in `crypto(7)` for more information about algorithm fetching. On exit `*in` will be updated to point to the next byte in the buffer after the decoded structure.

`ASN1_item_d2i()` is the same as `ASN1_item_d2i_ex()` except that the default `OSSL_LIB_CTX` is used (i.e. NULL) and with a NULL property query string.

`ASN1_item_d2i_bio_ex()` decodes the contents of its input BIO `in`, which must be a DER-encoded ASN.1 structure, using the ASN.1 template `it` and places the result in `*pval` unless `pval` is NULL. If `in` is NULL it returns NULL, else a pointer to the parsed structure. If any algorithm fetches are required during the process then they will use the `OSSL_LIB_CTX` provided in the `libctx` parameter and the property query string in `propq`. See "ALGORITHM FETCHING" in `crypto(7)` for more information about algorithm fetching.

ASN1_item_d2i_bio() is the same as ASN1_item_d2i_bio_ex() except that the default OSSL_LIB_CTX is used (i.e. NULL) and with a NULL property query string.

ASN1_item_d2i_fp_ex() is the same as ASN1_item_d2i_bio_ex() except that a FILE pointer is provided instead of a BIO.

ASN1_item_d2i_fp() is the same as ASN1_item_d2i_fp_ex() except that the default OSSL_LIB_CTX is used (i.e. NULL) and with a NULL property query string.

ASN1_item_i2d_mem_bio() encodes the given ASN.1 value val using the ASN.1 template it and returns the result in a memory BIO.

RETURN VALUES

ASN1_item_d2i_bio() returns a pointer to an ASN1_VALUE or NULL.

ASN1_item_i2d_mem_bio() returns a pointer to a memory BIO or NULL on error.

HISTORY

The functions ASN1_item_d2i_ex(), ASN1_item_d2i_bio_ex(), ASN1_item_d2i_fp_ex() and ASN1_item_i2d_mem_bio() were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

