



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ASN1_item_new_ex.3ossl'

\$ man ASN1_item_new_ex.3ossl

ASN1_ITEM_NEW(3ossl) OpenSSL ASN1_ITEM_NEW(3ossl)

NAME

ASN1_item_new_ex, ASN1_item_new - create new ASN.1 values

SYNOPSIS

```
#include <openssl/asn1.h>
```

```
ASN1_VALUE *ASN1_item_new_ex(const ASN1_ITEM *it, OSSL_LIB_CTX *libctx,  
                             const char *propq);
```

```
ASN1_VALUE *ASN1_item_new(const ASN1_ITEM *it);
```

DESCRIPTION

ASN1_item_new_ex() creates a new ASN1_VALUE structure based on the ASN1_ITEM template given in the it parameter. If any algorithm fetches are required during the process then they will use the OSSL_LIB_CTX provided in the libctx parameter and the property query string in propq. See "ALGORITHM FETCHING" in crypto(7) for more information about

algorithm fetching.

ASN1_item_new() is the same as ASN1_item_new_ex() except that the default OSSL_LIB_CTX is used (i.e. NULL) and with a NULL property query string.

RETURN VALUES

ASN1_item_new_ex() and ASN1_item_new() return a pointer to the newly created ASN1_VALUE or NULL on error.

HISTORY

The function ASN1_item_new_ex() was added in OpenSSL 3.0.

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 ASN1_ITEM_NEW(3ossl)