



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'BIO\_free\_all.3ossl'***

***\$ man BIO\_free\_all.3ossl***

BIO\_NEW(3ossl)                      OpenSSL                      BIO\_NEW(3ossl)

#### NAME

BIO\_new\_ex, BIO\_new, BIO\_up\_ref, BIO\_free, BIO\_vfree, BIO\_free\_all -  
BIO allocation and freeing functions

#### SYNOPSIS

```
#include <openssl/bio.h>
```

```
BIO *BIO_new_ex(OSSL_LIB_CTX *libctx, const BIO_METHOD *type);
```

```
BIO *BIO_new(const BIO_METHOD *type);
```

```
int BIO_up_ref(BIO *a);
```

```
int BIO_free(BIO *a);
```

```
void BIO_vfree(BIO *a);
```

```
void BIO_free_all(BIO *a);
```

#### DESCRIPTION

The BIO\_new\_ex() function returns a new BIO using method type

associated with the library context libctx (see OSSL\_LIB\_CTX(3)). The library context may be NULL to indicate the default library context.

The BIO\_new() is the same as BIO\_new\_ex() except the default library context is always used.

BIO\_up\_ref() increments the reference count associated with the BIO object.

BIO\_free() frees up a single BIO, BIO\_vfree() also frees up a single BIO but it does not return a value. If a is NULL nothing is done. Calling BIO\_free() may also have some effect on the underlying I/O structure, for example it may close the file being referred to under certain circumstances. For more details see the individual BIO\_METHOD descriptions.

BIO\_free\_all() frees up an entire BIO chain, it does not halt if an error occurs freeing up an individual BIO in the chain. If a is NULL nothing is done.

## RETURN VALUES

BIO\_new\_ex() and BIO\_new() return a newly created BIO or NULL if the call fails.

BIO\_up\_ref() and BIO\_free() return 1 for success and 0 for failure.

BIO\_free\_all() and BIO\_vfree() do not return values.

## NOTES

If BIO\_free() is called on a BIO chain it will only free one BIO resulting in a memory leak.

Calling BIO\_free\_all() on a single BIO has the same effect as calling

BIO\_free() on it other than the discarded return value.

## HISTORY

BIO\_set() was removed in OpenSSL 1.1.0 as BIO type is now opaque.

BIO\_new\_ex() was added in OpenSSL 3.0.

## EXAMPLES

Create a memory BIO:

```
BIO *mem = BIO_new(BIO_s_mem());
```

## COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7

2023-07-13

BIO\_NEW(3ossl)