



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'BIO\_s\_socket.3ossl'***

***\$ man BIO\_s\_socket.3ossl***

BIO\_S\_SOCKET(3ossl)          OpenSSL          BIO\_S\_SOCKET(3ossl)

#### NAME

BIO\_s\_socket, BIO\_new\_socket - socket BIO

#### SYNOPSIS

```
#include <openssl/bio.h>
```

```
const BIO_METHOD *BIO_s_socket(void);
```

```
BIO *BIO_new_socket(int sock, int close_flag);
```

#### DESCRIPTION

BIO\_s\_socket() returns the socket BIO method. This is a wrapper round the platform's socket routines.

BIO\_read\_ex() and BIO\_write\_ex() read or write the underlying socket.

BIO\_puts() is supported but BIO\_gets() is not.

If the close flag is set then the socket is shut down and closed when the BIO is freed.

BIO\_new\_socket() returns a socket BIO using sock and close\_flag.

## NOTES

Socket BIOs also support any relevant functionality of file descriptor BIOs.

The reason for having separate file descriptor and socket BIOs is that on some platforms sockets are not file descriptors and use distinct I/O routines, Windows is one such platform. Any code mixing the two will not work on all platforms.

## RETURN VALUES

BIO\_s\_socket() returns the socket BIO method.

BIO\_new\_socket() returns the newly allocated BIO or NULL is an error occurred.

## COPYRIGHT

Copyright 2000-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.