



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'BN\_native2bn.3ossl'***

***\$ man BN\_native2bn.3ossl***

BN\_BN2BIN(3ossl)            OpenSSL            BN\_BN2BIN(3ossl)

NAME

BN\_bn2binpad, BN\_bn2bin, BN\_bin2bn, BN\_bn2lebinpad, BN\_lebin2bn,  
BN\_bn2nativepad, BN\_native2bn, BN\_bn2hex, BN\_bn2dec, BN\_hex2bn,  
BN\_dec2bn, BN\_print, BN\_print\_fp, BN\_bn2mpi, BN\_mpi2bn - format  
conversions

SYNOPSIS

```
#include <openssl/bn.h>

int BN_bn2bin(const BIGNUM *a, unsigned char *to);

int BN_bn2binpad(const BIGNUM *a, unsigned char *to, int tolen);

BIGNUM *BN_bin2bn(const unsigned char *s, int len, BIGNUM *ret);

int BN_bn2lebinpad(const BIGNUM *a, unsigned char *to, int tolen);

BIGNUM *BN_lebin2bn(const unsigned char *s, int len, BIGNUM *ret);

int BN_bn2nativepad(const BIGNUM *a, unsigned char *to, int tolen);

BIGNUM *BN_native2bn(const unsigned char *s, int len, BIGNUM *ret);

char *BN_bn2hex(const BIGNUM *a);

char *BN_bn2dec(const BIGNUM *a);

int BN_hex2bn(BIGNUM **a, const char *str);
```

```
int BN_dec2bn(BIGNUM **a, const char *str);
int BN_print(BIO *fp, const BIGNUM *a);
int BN_print_fp(FILE *fp, const BIGNUM *a);
int BN_bn2mpi(const BIGNUM *a, unsigned char *to);
BIGNUM *BN_mpi2bn(unsigned char *s, int len, BIGNUM *ret);
```

## DESCRIPTION

BN\_bn2bin() converts the absolute value of a into big-endian form and stores it at to. to must point to BN\_num\_bytes(a) bytes of memory.

BN\_bn2binpad() also converts the absolute value of a into big-endian form and stores it at to. tolen indicates the length of the output buffer to. The result is padded with zeros if necessary. If tolen is less than BN\_num\_bytes(a) an error is returned.

BN\_bin2bn() converts the positive integer in big-endian form of length len at s into a BIGNUM and places it in ret. If ret is NULL, a new BIGNUM is created.

BN\_bn2lebinpad() and BN\_lebin2bn() are identical to BN\_bn2binpad() and BN\_bin2bn() except the buffer is in little-endian format.

BN\_bn2nativepad() and BN\_native2bn() are identical to BN\_bn2binpad() and BN\_bin2bn() except the buffer is in native format, i.e. most significant byte first on big-endian platforms, and least significant byte first on little-endian platforms.

BN\_bn2hex() and BN\_bn2dec() return printable strings containing the hexadecimal and decimal encoding of a respectively. For negative numbers, the string is prefaced with a leading '-'. The string must be freed later using OPENSSL\_free().

BN\_hex2bn() takes as many characters as possible from the string str, including the leading character '-' which means negative, to form a valid hexadecimal number representation and converts them to a BIGNUM and stores it in \*\*a. If \*a is NULL, a new BIGNUM is created. If a is NULL, it only computes the length of valid representation. A "negative zero" is converted to zero. BN\_dec2bn() is the same using the decimal system.

BN\_print() and BN\_print\_fp() write the hexadecimal encoding of a, with

a leading '-' for negative numbers, to the BIO or FILE fp.

BN\_bn2mpi() and BN\_mpi2bn() convert BIGNUMs from and to a format that consists of the number's length in bytes represented as a 4-byte big-endian number, and the number itself in big-endian format, where the most significant bit signals a negative number (the representation of numbers with the MSB set is prefixed with null byte).

BN\_bn2mpi() stores the representation of a at to, where to must be large enough to hold the result. The size can be determined by calling BN\_bn2mpi(a, NULL).

BN\_mpi2bn() converts the len bytes long representation at s to a BIGNUM and stores it at ret, or in a newly allocated BIGNUM if ret is NULL.

## RETURN VALUES

BN\_bn2bin() returns the length of the big-endian number placed at to.

BN\_bin2bn() returns the BIGNUM, NULL on error.

BN\_bn2binpad(), BN\_bn2lebinpad(), and BN\_bn2nativepad() return the number of bytes written or -1 if the supplied buffer is too small.

BN\_bn2hex() and BN\_bn2dec() return a NUL-terminated string, or NULL on error. BN\_hex2bn() and BN\_dec2bn() return the number of characters used in parsing, or 0 on error, in which case no new BIGNUM will be created.

BN\_print\_fp() and BN\_print() return 1 on success, 0 on write errors.

BN\_bn2mpi() returns the length of the representation. BN\_mpi2bn() returns the BIGNUM, and NULL on error.

The error codes can be obtained by ERR\_get\_error(3).

## SEE ALSO

ERR\_get\_error(3), BN\_zero(3), ASN1\_INTEGER\_to\_BN(3), BN\_num\_bytes(3)

## COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at

<<https://www.openssl.org/source/license.html>>.