



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'CMS_add1_crl.3oss1'

\$ man CMS_add1_crl.3oss1

CMS_ADD0_CERT(3oss1) OpenSSL CMS_ADD0_CERT(3oss1)

NAME

CMS_add0_cert, CMS_add1_cert, CMS_get1_certs, CMS_add0_crl,
CMS_add1_crl, CMS_get1_crls - CMS certificate and CRL utility functions

SYNOPSIS

```
#include <openssl/cms.h>
```

```
int CMS_add0_cert(CMS_ContentInfo *cms, X509 *cert);  
int CMS_add1_cert(CMS_ContentInfo *cms, X509 *cert);  
STACK_OF(X509) *CMS_get1_certs(CMS_ContentInfo *cms);
```

```
int CMS_add0_crl(CMS_ContentInfo *cms, X509_CRL *crl);  
int CMS_add1_crl(CMS_ContentInfo *cms, X509_CRL *crl);  
STACK_OF(X509_CRL) *CMS_get1_crls(CMS_ContentInfo *cms);
```

DESCRIPTION

CMS_add0_cert() and CMS_add1_cert() add certificate cert to cms. cms must be of type signed data or (authenticated) enveloped data. For signed data, such a certificate can be used when signing or verifying to fill in the signer certificate or to provide an extra CA certificate that may be needed for chain building in certificate validation.

CMS_get1_certs() returns all certificates in cms.

CMS_add0_crl() and CMS_add1_crl() add CRL crl to cms. cms must be of type signed data or (authenticated) enveloped data. For signed data, such a CRL may be used in certificate validation. It may be given both for inclusion when signing a CMS message and when verifying a signed CMS message.

CMS_get1_crls() returns all CRLs in cms.

NOTES

The CMS_ContentInfo structure cms must be of type signed data or enveloped data or an error will be returned.

For signed data certificates and CRLs are added to the certificates and crls fields of SignedData structure. For enveloped data they are added to OriginatorInfo.

As the 0 implies CMS_add0_cert() adds cert internally to cms and it must not be freed up after the call as opposed to CMS_add1_cert() where cert must be freed up.

The same certificate or CRL must not be added to the same cms structure more than once.

RETURN VALUES

CMS_add0_cert(), CMS_add1_cert() and CMS_add0_crl() and CMS_add1_crl()

return 1 for success and 0 for failure.

CMS_get1_certs() and CMS_get1_crls() return the STACK of certificates or CRLs or NULL if there are none or an error occurs. The only error which will occur in practice is if the cms type is invalid.

SEE ALSO

ERR_get_error(3), CMS_sign(3), CMS_encrypt(3)

COPYRIGHT

Copyright 2008-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 CMS_ADD0_CERT(3ossl)