



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'CRYPTO\_atomic\_load.3oss1'***

***\$ man CRYPTO\_atomic\_load.3oss1***

CRYPTO\_THREAD\_RUN\_ONCE(3oss1)    OpenSSL    CRYPTO\_THREAD\_RUN\_ONCE(3oss1)

NAME

CRYPTO\_THREAD\_run\_once, CRYPTO\_THREAD\_lock\_new,  
CRYPTO\_THREAD\_read\_lock, CRYPTO\_THREAD\_write\_lock,  
CRYPTO\_THREAD\_unlock, CRYPTO\_THREAD\_lock\_free, CRYPTO\_atomic\_add,  
CRYPTO\_atomic\_or, CRYPTO\_atomic\_load - OpenSSL thread support

SYNOPSIS

```
#include <openssl/crypto.h>

CRYPTO_ONCE CRYPTO_ONCE_STATIC_INIT;

int CRYPTO_THREAD_run_once(CRYPTO_ONCE *once, void (*init)(void));

CRYPTO_RWLOCK *CRYPTO_THREAD_lock_new(void);

int CRYPTO_THREAD_read_lock(CRYPTO_RWLOCK *lock);

int CRYPTO_THREAD_write_lock(CRYPTO_RWLOCK *lock);

int CRYPTO_THREAD_unlock(CRYPTO_RWLOCK *lock);

void CRYPTO_THREAD_lock_free(CRYPTO_RWLOCK *lock);

int CRYPTO_atomic_add(int *val, int amount, int *ret, CRYPTO_RWLOCK *lock);

int CRYPTO_atomic_or(uint64_t *val, uint64_t op, uint64_t *ret,
                    CRYPTO_RWLOCK *lock);
```

```
int CRYPTO_atomic_load(uint64_t *val, uint64_t *ret, CRYPTO_RWLOCK *lock);
```

## DESCRIPTION

OpenSSL can be safely used in multi-threaded applications provided that support for the underlying OS threading API is built-in. Currently, OpenSSL supports the pthread and Windows APIs. OpenSSL can also be built without any multi-threading support, for example on platforms that don't provide any threading support or that provide a threading API that is not yet supported by OpenSSL.

The following multi-threading function are provided:

? CRYPTO\_THREAD\_run\_once() can be used to perform one-time initialization. The once argument must be a pointer to a static object of type CRYPTO\_ONCE that was statically initialized to the value CRYPTO\_ONCE\_STATIC\_INIT. The init argument is a pointer to a function that performs the desired exactly once initialization. In particular, this can be used to allocate locks in a thread-safe manner, which can then be used with the locking functions below.

? CRYPTO\_THREAD\_lock\_new() allocates, initializes and returns a new read/write lock.

? CRYPTO\_THREAD\_read\_lock() locks the provided lock for reading.

? CRYPTO\_THREAD\_write\_lock() locks the provided lock for writing.

? CRYPTO\_THREAD\_unlock() unlocks the previously locked lock.

? CRYPTO\_THREAD\_lock\_free() frees the provided lock.

? CRYPTO\_atomic\_add() atomically adds amount to \*val and returns the result of the operation in \*ret. lock will be locked, unless atomic operations are supported on the specific platform. Because of this, if a variable is modified by CRYPTO\_atomic\_add() then CRYPTO\_atomic\_add() must be the only way that the variable is modified. If atomic operations are not supported and lock is NULL, then the function will fail.

? CRYPTO\_atomic\_or() performs an atomic bitwise or of op and \*val and stores the result back in \*val. It also returns the result of the operation in \*ret. lock will be locked, unless atomic operations are supported on the specific platform. Because of this, if a variable is

modified by CRYPTO\_atomic\_or() or read by CRYPTO\_atomic\_load() then CRYPTO\_atomic\_or() must be the only way that the variable is modified. If atomic operations are not supported and lock is NULL, then the function will fail.

? CRYPTO\_atomic\_load() atomically loads the contents of \*val into \*ret.

lock will be locked, unless atomic operations are supported on the specific platform. Because of this, if a variable is modified by CRYPTO\_atomic\_or() or read by CRYPTO\_atomic\_load() then CRYPTO\_atomic\_load() must be the only way that the variable is read.

If atomic operations are not supported and lock is NULL, then the function will fail.

## RETURN VALUES

CRYPTO\_THREAD\_run\_once() returns 1 on success, or 0 on error.

CRYPTO\_THREAD\_lock\_new() returns the allocated lock, or NULL on error.

CRYPTO\_THREAD\_lock\_free() returns no value.

The other functions return 1 on success, or 0 on error.

## NOTES

On Windows platforms the CRYPTO\_THREAD\_\* types and functions in the <openssl/crypto.h> header are dependent on some of the types customarily made available by including <windows.h>. The application developer is likely to require control over when the latter is included, commonly as one of the first included headers. Therefore, it is defined as an application developer's responsibility to include <windows.h> prior to <openssl/crypto.h> where use of CRYPTO\_THREAD\_\* types and functions is required.

## EXAMPLES

You can find out if OpenSSL was configured with thread support:

```
#include <openssl/opensslconf.h>
#if defined(OPENSSL_THREADS)
    /* thread support enabled */
#else
    /* no thread support */
#endif
```

This example safely initializes and uses a lock.

```
#ifdef _WIN32
# include <windows.h>
#endif

#include <openssl/crypto.h>

static CRYPTO_ONCE once = CRYPTO_ONCE_STATIC_INIT;
static CRYPTO_RWLOCK *lock;

static void myinit(void)
{
    lock = CRYPTO_THREAD_lock_new();
}

static int mylock(void)
{
    if (!CRYPTO_THREAD_run_once(&once, void init) || lock == NULL)
        return 0;
    return CRYPTO_THREAD_write_lock(lock);
}

static int myunlock(void)
{
    return CRYPTO_THREAD_unlock(lock);
}

int serialized(void)
{
    int ret = 0;
    if (mylock()) {
        /* Your code here, do not return without releasing the lock! */
        ret = ... ;
    }
    myunlock();
    return ret;
}
```

Finalization of locks is an advanced topic, not covered in this example. This can only be done at process exit or when a dynamically

loaded library is no longer in use and is unloaded. The simplest solution is to just "leak" the lock in applications and not repeatedly load/unload shared libraries that allocate locks.

#### SEE ALSO

crypto(7), openssl-threads(7).

#### COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.  
Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13    CRYPTO\_THREAD\_RUN\_ONCE(3ossl)