



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'DTLS_timer_cb.3ossl'

\$ man DTLS_timer_cb.3ossl

DTLS_SET_TIMER_CB(3ossl) OpenSSL DTLS_SET_TIMER_CB(3ossl)

NAME

DTLS_timer_cb, DTLS_set_timer_cb - Set callback for controlling DTLS timer duration

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
typedef unsigned int (*DTLS_timer_cb)(SSL *s, unsigned int timer_us);
```

```
void DTLS_set_timer_cb(SSL *s, DTLS_timer_cb cb);
```

DESCRIPTION

This function sets an optional callback function for controlling the timeout interval on the DTLS protocol. The callback function will be called by DTLS for every new DTLS packet that is sent.

RETURN VALUES

Returns void.

HISTORY

The `DTLS_set_timer_cb()` function was added in OpenSSL 1.1.1.

COPYRIGHT

Copyright 2017 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 DTLS_SET_TIMER_CB(3ossl)