



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ERR_pop_to_mark.3ossl'

\$ man ERR_pop_to_mark.3ossl

ERR_SET_MARK(3ossl) OpenSSL ERR_SET_MARK(3ossl)

NAME

ERR_set_mark, ERR_clear_last_mark, ERR_pop_to_mark - set mark, clear mark and pop errors until mark

SYNOPSIS

```
#include <openssl/err.h>
```

```
int ERR_set_mark(void);
```

```
int ERR_pop_to_mark(void);
```

```
int ERR_clear_last_mark(void);
```

DESCRIPTION

ERR_set_mark() sets a mark on the current topmost error record if there is one.

ERR_pop_to_mark() will pop the top of the error stack until a mark is

found. The mark is then removed. If there is no mark, the whole stack is removed.

`ERR_clear_last_mark()` removes the last mark added if there is one.

RETURN VALUES

`ERR_set_mark()` returns 0 if the error stack is empty, otherwise 1.

`ERR_clear_last_mark()` and `ERR_pop_to_mark()` return 0 if there was no mark in the error stack, which implies that the stack became empty, otherwise 1.

COPYRIGHT

Copyright 2003-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 ERR_SET_MARK(3ossl)