



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'EVP_KDF-TLS13_KDF.7ossl'

\$ man EVP_KDF-TLS13_KDF.7ossl

EVP_KDF-TLS13_KDF(7ossl) OpenSSL EVP_KDF-TLS13_KDF(7ossl)

NAME

EVP_KDF-TLS13_KDF - The TLS 1.3 EVP_KDF implementation

DESCRIPTION

Support for computing the TLS 1.3 version of the HKDF KDF through the EVP_KDF API.

The EVP_KDF-TLS13_KDF algorithm implements the HKDF key derivation function as used by TLS 1.3.

Identity

"TLS13-KDF" is the name for this implementation; it can be used with the EVP_KDF_fetch() function.

Supported parameters

The supported parameters are:

"properties" (OSSL_KDF_PARAM_PROPERTIES) <UTF8 string>

"digest" (OSSL_KDF_PARAM_DIGEST) <UTF8 string>

"key" (OSSL_KDF_PARAM_KEY) <octet string>

"salt" (OSSL_KDF_PARAM_SALT) <octet string>

These parameters work as described in "PARAMETERS" in EVP_KDF(3).

"prefix" (OSSL_KDF_PARAM_PREFIX) <octet string>

This parameter sets the label prefix on the specified TLS 1.3 KDF context. For TLS 1.3 this should be set to the ASCII string "tls13" without a trailing zero byte. Refer to RFC 8446 section 7.1 "Key Schedule" for details.

"label" (OSSL_KDF_PARAM_LABEL) <octet string>

This parameter sets the label on the specified TLS 1.3 KDF context. Refer to RFC 8446 section 7.1 "Key Schedule" for details.

"data" (OSSL_KDF_PARAM_DATA) <octet string>

This parameter sets the context data on the specified TLS 1.3 KDF context. Refer to RFC 8446 section 7.1 "Key Schedule" for details.

"mode" (OSSL_KDF_PARAM_MODE) <UTF8 string> or <integer>

This parameter sets the mode for the TLS 1.3 KDF operation. There are two modes that are currently defined:

"EXTRACT_ONLY" or EVP_KDF_HKDF_MODE_EXTRACT_ONLY

In this mode calling EVP_KDF_derive(3) will just perform the extract operation. The value returned will be the intermediate fixed-length pseudorandom key K. The keylen parameter must match the size of K, which can be looked up by calling EVP_KDF_CTX_get_kdf_size() after setting the mode and digest.

The digest, key and salt values must be set before a key is

derived otherwise an error will occur.

"EXPAND_ONLY" or EVP_KDF_HKDF_MODE_EXPAND_ONLY

In this mode calling EVP_KDF_derive(3) will just perform the expand operation. The input key should be set to the intermediate fixed-length pseudorandom key K returned from a previous extract operation.

The digest, key and info values must be set before a key is derived otherwise an error will occur.

NOTES

This KDF is intended for use by the TLS 1.3 implementation in libssl. It does not support all the options and capabilities that HKDF does.

The OSSL_PARAM array passed to EVP_KDF_derive(3) or EVP_KDF_CTX_set_params(3) must specify all of the parameters required. This KDF does not support a piecemeal approach to providing these.

A context for a TLS 1.3 KDF can be obtained by calling:

```
EVP_KDF *kdf = EVP_KDF_fetch(NULL, "TLS13-KDF", NULL);  
EVP_KDF_CTX *kctx = EVP_KDF_CTX_new(kdf);
```

The output length of a TLS 1.3 KDF expand operation is specified via the keylen parameter to the EVP_KDF_derive(3) function. When using EVP_KDF_HKDF_MODE_EXTRACT_ONLY the keylen parameter must equal the size of the intermediate fixed-length pseudorandom key otherwise an error will occur. For that mode, the fixed output size can be looked up by calling EVP_KDF_CTX_get_kdf_size() after setting the mode and digest on the EVP_KDF_CTX.

SEE ALSO

EVP_KDF(3), EVP_KDF_CTX_new(3), EVP_KDF_CTX_free(3),
EVP_KDF_CTX_get_kdf_size(3), EVP_KDF_CTX_set_params(3),
EVP_KDF_derive(3), "PARAMETERS" in EVP_KDF(3), EVP_KDF-HKDF(7)

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use
this file except in compliance with the License. You can obtain a copy
in the file LICENSE in the source distribution or at
<<https://www.openssl.org/source/license.html>>.

3.0.7 2023-07-13 EVP_KDF-TLS13_KDF(7ossl)