



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'EVP_PKEY2PKCS8.3ossl'

\$ man EVP_PKEY2PKCS8.3ossl

EVP_PKEY2PKCS8(3ossl) OpenSSL EVP_PKEY2PKCS8(3ossl)

NAME

EVP_PKEY2PKCS8, EVP_PKCS82PKEY_ex, EVP_PKCS82PKEY - Convert a private key to/from PKCS8

SYNOPSIS

```
#include <openssl/x509.h>
```

```
PKCS8_PRIV_KEY_INFO *EVP_PKEY2PKCS8(const EVP_PKEY *pkey);  
EVP_PKEY *EVP_PKCS82PKEY(const PKCS8_PRIV_KEY_INFO *p8);  
EVP_PKEY *EVP_PKCS82PKEY_ex(const PKCS8_PRIV_KEY_INFO *p8, OSSL_LIB_CTX *libctx,  
                             const char *propq);
```

DESCRIPTION

EVP_PKEY2PKCS8() converts a private key pkey into a returned PKCS8 object.

EVP_PKCS82PKEY_ex() converts a PKCS8 object p8 into a returned private key. It uses libctx and propq when fetching algorithms.

EVP_PKCS82PKEY() is similar to EVP_PKCS82PKEY_ex() but uses default values of NULL for the libctx and propq.

RETURN VALUES

EVP_PKEY2PKCS8() returns a PKCS8 object on success. EVP_PKCS82PKEY() and EVP_PKCS82PKEY_ex() return a private key on success.

All functions return NULL if the operation fails.

SEE ALSO

PKCS8_pkey_add1_attr(3),

COPYRIGHT

Copyright 2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 EVP_PKEY2PKCS8(3ossl)