



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'EVP_PKEY_decapsulate_init.3ossl'

\$ man EVP_PKEY_decapsulate_init.3ossl

EVP_PKEY_DECAPSULATE(3ossl) OpenSSL EVP_PKEY_DECAPSULATE(3ossl)

NAME

EVP_PKEY_decapsulate_init, EVP_PKEY_decapsulate - Key decapsulation
using a private key algorithm

SYNOPSIS

```
#include <openssl/evp.h>
```

```
int EVP_PKEY_decapsulate_init(EVP_PKEY_CTX *ctx, const OSSL_PARAM params[]);
```

```
int EVP_PKEY_decapsulate(EVP_PKEY_CTX *ctx,  
                          unsigned char *secret, size_t *secretlen,  
                          const unsigned char *wrapped, size_t wrappedlen);
```

DESCRIPTION

The EVP_PKEY_decapsulate_init() function initializes a private key algorithm context ctx for a decapsulation operation and then sets the params on the context in the same way as calling

EVP_PKEY_CTX_set_params(3).

The EVP_PKEY_decapsulate() function performs a private key decapsulation operation using ctx. The data to be decapsulated is specified using the wrapped and wrappedlen parameters. If secret is NULL then the maximum size of the output secret buffer is written to the *secretlen parameter. If secret is not NULL and the call is successful then the decapsulated secret data is written to secret and the amount of data written to secretlen.

NOTES

After the call to EVP_PKEY_decapsulate_init() algorithm specific parameters for the operation may be set or modified using EVP_PKEY_CTX_set_params(3).

RETURN VALUES

EVP_PKEY_decapsulate_init() and EVP_PKEY_decapsulate() return 1 for success and 0 or a negative value for failure. In particular a return value of -2 indicates the operation is not supported by the private key algorithm.

EXAMPLES

Decapsulate data using RSA:

```
#include <openssl/evp.h>
```

```
/*
```

```
 * NB: assumes rsa_priv_key is an RSA private key,
```

```
 * and that in, inlen are already set up to contain encapsulated data.
```

```
*/
```

```
EVP_PKEY_CTX *ctx = NULL;
```

```
size_t secretlen = 0;
```

```

unsigned char *secret = NULL;;

ctx = EVP_PKEY_CTX_new_from_pkey(libctx, rsa_priv_key, NULL);
if (ctx = NULL)
    /* Error */
if (EVP_PKEY_decapsulate_init(ctx, NULL) <= 0)
    /* Error */

/* Set the mode - only 'RSASVE' is currently supported */
if (EVP_PKEY_CTX_set_kem_op(ctx, "RSASVE") <= 0)
    /* Error */

/* Determine buffer length */
if (EVP_PKEY_decapsulate(ctx, NULL, &secretlen, in, inlen) <= 0)
    /* Error */

secret = OPENSSL_malloc(secretlen);
if (secret == NULL)
    /* malloc failure */

/* Decapsulated secret data is secretlen bytes long */
if (EVP_PKEY_decapsulate(ctx, secret, &secretlen, in, inlen) <= 0)
    /* Error */

```

SEE ALSO

EVP_PKEY_CTX_new(3), EVP_PKEY_encapsulate(3), EVP_KEM-RSA(7),

HISTORY

These functions were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2020-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 EVP_PKEY_DECAPSULATE(3ossl)