



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'EVP_SIGNATURE-CMAC.7oss1'

\$ man EVP_SIGNATURE-CMAC.7oss1

EVP_SIGNATURE-HMAC(7oss1) OpenSSL EVP_SIGNATURE-HMAC(7oss1)

NAME

EVP_SIGNATURE-HMAC, EVP_SIGNATURE-Siphash, EVP_SIGNATURE-Poly1305,
EVP_SIGNATURE-CMAC - The legacy EVP_PKEY MAC signature implementations

DESCRIPTION

The algorithms described here have legacy support for creating MACs using EVP_DigestSignInit(3) and related functions. This is not the preferred way of creating MACs. Instead you should use the newer EVP_MAC_init(3) functions. This mechanism is provided for backwards compatibility with older versions of OpenSSL.

The same signature parameters can be set using EVP_PKEY_CTX_set_params() as can be set via EVP_MAC_CTX_set_params() for the underlying EVP_MAC. See EVP_MAC-HMAC(7), EVP_MAC-Siphash(7), EVP_MAC-Poly1305(7) and EVP_MAC-CMAC(7) for details.

See L<EVP_PKEY-HMAC(7)>, L<EVP_PKEY-Siphash(7)>, L<EVP_PKEY-Poly1305(7)> or L<EVP_PKEY-CMAC(7)> for details about parameters that are supported during the creation of an EVP_PKEY.

SEE ALSO

EVP_MAC_init(3), EVP_DigestSignInit(3), EVP_PKEY-HMAC(7),
EVP_PKEY-Siphash(7), EVP_PKEY-Poly1305(7), EVP_PKEY-CMAC(7),
EVP_MAC-HMAC(7), EVP_MAC-Siphash(7), EVP_MAC-Poly1305(7),
EVP_MAC-CMAC(7), provider-signature(7),

COPYRIGHT

Copyright 2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.

3.0.7 2023-07-13 EVP_SIGNATURE-HMAC(7ossl)