



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'EVP\_SignFinal.3ossl'***

***\$ man EVP\_SignFinal.3ossl***

EVP\_SIGNINIT(3ossl)          OpenSSL          EVP\_SIGNINIT(3ossl)

#### NAME

EVP\_SignInit, EVP\_SignInit\_ex, EVP\_SignUpdate, EVP\_SignFinal\_ex,  
EVP\_SignFinal - EVP signing functions

#### SYNOPSIS

```
#include <openssl/evp.h>
```

```
int EVP_SignInit_ex(EVP_MD_CTX *ctx, const EVP_MD *type, ENGINE *impl);
```

```
int EVP_SignUpdate(EVP_MD_CTX *ctx, const void *d, unsigned int cnt);
```

```
int EVP_SignFinal_ex(EVP_MD_CTX *ctx, unsigned char *md, unsigned int *s,
```

```
          EVP_PKEY *pkey, OSSL_LIB_CTX *libctx, const char *propq);
```

```
int EVP_SignFinal(EVP_MD_CTX *ctx, unsigned char *sig, unsigned int *s,
```

```
          EVP_PKEY *pkey);
```

```
void EVP_SignInit(EVP_MD_CTX *ctx, const EVP_MD *type);
```

## DESCRIPTION

The EVP signature routines are a high-level interface to digital signatures.

`EVP_SignInit_ex()` sets up signing context `ctx` to use digest type from `ENGINE` impl. `ctx` must be created with `EVP_MD_CTX_new()` before calling this function.

`EVP_SignUpdate()` hashes `cnt` bytes of data at `d` into the signature context `ctx`. This function can be called several times on the same `ctx` to include additional data.

`EVP_SignFinal_ex()` signs the data in `ctx` using the private key `pkey` and places the signature in `sig`. The library context `libctx` and property query `propq` are used when creating a context to use with the key `pkey`. `sig` must be at least "`EVP_PKEY_get_size(pkey)`" bytes in size. `s` is an `OUT` parameter, and not used as an `IN` parameter. The number of bytes of data written (i.e. the length of the signature) will be written to the integer at `s`, at most "`EVP_PKEY_get_size(pkey)`" bytes will be written.

`EVP_SignFinal()` is similar to `EVP_SignFinal_ex()` but uses default values of `NULL` for the library context `libctx` and the property query `propq`.

`EVP_SignInit()` initializes a signing context `ctx` to use the default implementation of digest type.

## RETURN VALUES

`EVP_SignInit_ex()`, `EVP_SignUpdate()`, `EVP_SignFinal_ex()` and `EVP_SignFinal()` return 1 for success and 0 for failure.

The error codes can be obtained by `ERR_get_error(3)`.

## NOTES

The EVP interface to digital signatures should almost always be used in preference to the low-level interfaces. This is because the code then becomes transparent to the algorithm used and much more flexible.

When signing with DSA private keys the random number generator must be seeded. If the automatic seeding or reseeding of the OpenSSL CSPRNG fails due to external circumstances (see RAND(7)), the operation will fail. This requirement does not hold for RSA signatures.

The call to `EVP_SignFinal()` internally finalizes a copy of the digest context. This means that calls to `EVP_SignUpdate()` and `EVP_SignFinal()` can be called later to digest and sign additional data.

Since only a copy of the digest context is ever finalized the context must be cleaned up after use by calling `EVP_MD_CTX_free()` or a memory leak will occur.

## BUGS

Older versions of this documentation wrongly stated that calls to `EVP_SignUpdate()` could not be made after calling `EVP_SignFinal()`.

Since the private key is passed in the call to `EVP_SignFinal()` any error relating to the private key (for example an unsuitable key and digest combination) will not be indicated until after potentially large amounts of data have been passed through `EVP_SignUpdate()`.

It is not possible to change the signing parameters using these function.

The previous two bugs are fixed in the newer `EVP_SignDigest*()` function.

## SEE ALSO

EVP\_PKEY\_get\_size(3), EVP\_PKEY\_get\_bits(3),  
EVP\_PKEY\_get\_security\_bits(3), EVP\_VerifyInit(3), EVP\_DigestInit(3),  
evp(7), HMAC(3), MD2(3), MD5(3), MDC2(3), RIPEMD160(3), SHA1(3),  
openssl-dgst(1)

## HISTORY

The function `EVP_SignFinal_ex()` was added in OpenSSL 3.0.

## COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use  
this file except in compliance with the License. You can obtain a copy  
in the file LICENSE in the source distribution or at  
<<https://www.openssl.org/source/license.html>>.

3.0.7                      2023-07-13                      EVP\_SIGNINIT(3ossl)