



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'OCSP\_sendreq\_bio.3ossl'***

***\$ man OCSP\_sendreq\_bio.3ossl***

OCSP\_SENDREQ\_NEW(3ossl)      OpenSSL      OCSP\_SENDREQ\_NEW(3ossl)

NAME

OCSP\_REQ\_CTX, OCSP\_sendreq\_new, OCSP\_sendreq\_nbio, OCSP\_sendreq\_bio, OCSP\_REQ\_CTX\_i2d, OCSP\_REQ\_CTX\_add1\_header, OCSP\_REQ\_CTX\_free, OCSP\_set\_max\_response\_length, OCSP\_REQ\_CTX\_set1\_req - OCSP responder query functions

SYNOPSIS

```
#include <openssl/ocsp.h>
```

```
OSSL_HTTP_REQ_CTX *OCSP_sendreq_new(BIO *io, const char *path,
                                     const OCSP_REQUEST *req, int buf_size);
```

```
OCSP_RESPONSE *OCSP_sendreq_bio(BIO *io, const char *path, OCSP_REQUEST *req);
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL\_API\_COMPAT with a suitable version value, see openssl\_user\_macros(7):

```
typedef OSSL_HTTP_REQ_CTX OCSP_REQ_CTX;
```

```
int OCSP_sendreq_nbio(OCSP_RESPONSE **presp, OSSL_HTTP_REQ_CTX *rctx);
```

```
int OCSP_REQ_CTX_i2d(OCSP_REQ_CT *rctx, const ASN1_ITEM *it, ASN1_VALUE *req);
```

```
int OCSP_REQ_CTX_add1_header(OCSP_REQ_CT *rctx,
```

```

        const char *name, const char *value);
void OCSP_REQ_CTX_free(OCSP_REQ_CTX *rctx);
void OCSP_set_max_response_length(OCSP_REQ_CTX *rctx, unsigned long len);
int OCSP_REQ_CTX_set1_req(OCSP_REQ_CTX *rctx, const OCSP_REQUEST *req);

```

## DESCRIPTION

These functions perform an OCSP POST request / response transfer over HTTP, using the HTTP request functions described in OSSL\_HTTP\_REQ\_CTX(3).

The function OCSP\_sendreq\_new() builds a complete OSSL\_HTTP\_REQ\_CTX structure with the BIO io to be used for requests and response, the URL path path, optionally the OCSP request req, and a response header maximum line length of buf\_size. If buf\_size is zero a default value of 4KiB is used. The req may be set to NULL and provided later using OCSP\_REQ\_CTX\_set1\_req() or OSSL\_HTTP\_REQ\_CTX\_set1\_req(3). The io and path arguments to OCSP\_sendreq\_new() correspond to the components of the URL. For example if the responder URL is

"http://example.com/ocspreq" the BIO io should have been connected to host "example.com" on port 80 and path should be set to "/ocspreq".

OCSP\_sendreq\_nbio() attempts to send the request prepared in rctx and to gather the response via HTTP, using the BIO io and path that were given when calling OCSP\_sendreq\_new(). If the operation gets completed it assigns the response, a pointer to a OCSP\_RESPONSE structure, in \*presp. The function may need to be called again if its result is -1, which indicates BIO\_should\_retry(3). In such a case it is advisable to sleep a little in between, using BIO\_wait(3) on the read BIO to prevent a busy loop.

OCSP\_sendreq\_bio() combines OCSP\_sendreq\_new() with as many calls of OCSP\_sendreq\_nbio() as needed and then OCSP\_REQ\_CTX\_free(), with a response header maximum line length 4k. It waits indefinitely on a response. It does not support setting a timeout or adding headers and is retained for compatibility; use OSSL\_HTTP\_transfer(3) instead.

OCSP\_REQ\_CTX\_i2d(rctx, it, req) is equivalent to the following:

```
OSSL_HTTP_REQ_CTX_set1_req(rctx, "application/ocsp-request", it, req)
```

OCSP\_REQ\_CTX\_set1\_req(rctx, req) is equivalent to the following:

```
OSSL_HTTP_REQ_CTX_set1_req(rctx, "application/ocsp-request",
    ASN1_ITEM_rptr(OCSP_REQUEST),
    (const ASN1_VALUE *)req)
```

The deprecated type and the remaining deprecated functions have been superseded by the following equivalents: OCSP\_REQ\_CTX by OSSL\_HTTP\_REQ\_CTX(3), OCSP\_REQ\_CTX\_add1\_header() by OSSL\_HTTP\_REQ\_CTX\_add1\_header(3), OCSP\_REQ\_CTX\_free() by OSSL\_HTTP\_REQ\_CTX\_free(3), and OCSP\_set\_max\_response\_length() by OSSL\_HTTP\_REQ\_CTX\_set\_max\_response\_length(3).

## RETURN VALUES

OCSP\_sendreq\_new() returns a valid OSSL\_HTTP\_REQ\_CTX structure or NULL if an error occurred.

OCSP\_sendreq\_nbio() returns 1 for success, 0 on error, -1 if retry is needed.

OCSP\_sendreq\_bio() returns the OCSP\_RESPONSE structure sent by the responder or NULL if an error occurred.

## SEE ALSO

OSSL\_HTTP\_REQ\_CTX(3), OSSL\_HTTP\_transfer(3), OCSP\_cert\_to\_id(3), OCSP\_request\_add1\_nonce(3), OCSP\_REQUEST\_new(3), OCSP\_resp\_find\_status(3), OCSP\_response\_status(3)

## HISTORY

OCSP\_REQ\_CTX, OCSP\_REQ\_CTX\_i2d(), OCSP\_REQ\_CTX\_add1\_header(), OCSP\_REQ\_CTX\_free(), OCSP\_set\_max\_response\_length(), and OCSP\_REQ\_CTX\_set1\_req() were deprecated in OpenSSL 3.0.

## COPYRIGHT

Copyright 2015-2021 The OpenSSL Project Authors. All Rights Reserved.  
Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.