



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'PEM_X509_INFO_read_ex.3ossl'

\$ man PEM_X509_INFO_read_ex.3ossl

PEM_X509_INFO_READ_BIO_EX(3ossl) OpenSSL PEM_X509_INFO_READ_BIO_EX(3ossl)

NAME

PEM_X509_INFO_read_ex, PEM_X509_INFO_read, PEM_X509_INFO_read_bio_ex,
PEM_X509_INFO_read_bio - read PEM-encoded data structures into one or
more X509_INFO objects

SYNOPSIS

```
#include <openssl/pem.h>
```

```
STACK_OF(X509_INFO) *PEM_X509_INFO_read_ex(FILE *fp, STACK_OF(X509_INFO) *sk,  
pem_password_cb *cb, void *u,  
OSSL_LIB_CTX *libctx,  
const char *propq);
```

```
STACK_OF(X509_INFO) *PEM_X509_INFO_read(FILE *fp, STACK_OF(X509_INFO) *sk,  
pem_password_cb *cb, void *u);
```

```
STACK_OF(X509_INFO) *PEM_X509_INFO_read_bio_ex(BIO *bio,  
STACK_OF(X509_INFO) *sk,
```

```
    pem_password_cb *cb, void *u,  
    OSSL_LIB_CTX *libctx,  
    const char *propq);  
STACK_OF(X509_INFO) *PEM_X509_INFO_read_bio(BIO *bp, STACK_OF(X509_INFO) *sk,  
    pem_password_cb *cb, void *u);
```

DESCRIPTION

PEM_X509_INFO_read_ex() loads the X509_INFO objects from a file fp.

PEM_X509_INFO_read() is similar to PEM_X509_INFO_read_ex() but uses the default (NULL) library context libctx and empty property query propq.

PEM_X509_INFO_read_bio_ex() loads the X509_INFO objects using a bio bp.

PEM_X509_INFO_read_bio() is similar to PEM_X509_INFO_read_bio_ex() but uses the default (NULL) library context libctx and empty property query propq.

Each of the loaded X509_INFO objects can contain a CRL, a certificate, and/or a private key. The elements are read sequentially, and as far as they are of different type than the elements read before, they are combined into the same X509_INFO object. The idea behind this is that if, for instance, a certificate is followed by a private key, the private key is supposed to correspond to the certificate.

If the input stack sk is NULL a new stack is allocated, else the given stack is extended.

The optional cb and u parameters can be used for providing a passphrase needed for decrypting encrypted PEM structures (normally only private keys). See PEM_read_bio_PrivateKey(3) and passphrase-encoding(7) for details.

The library context libctx and property query propq are used for fetching algorithms from providers.

RETURN VALUES

PEM_X509_INFO_read_ex(), PEM_X509_INFO_read(), PEM_X509_INFO_read_bio_ex() and PEM_X509_INFO_read_bio() return a stack of X509_INFO objects or NULL on failure.

SEE ALSO

PEM_read_bio_ex(3), PEM_read_bio_PrivateKey(3), passphrase-encoding(7)

HISTORY

The functions PEM_X509_INFO_read_ex() and PEM_X509_INFO_read_bio_ex() were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2020-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 PEM_X509_INFO_READ_BIO_EX(3openssl)