



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'PKCS12\_get\_friendlyname.3ossl'***

***\$ man PKCS12\_get\_friendlyname.3ossl***

PKCS12\_GET\_FRIENDLYNAME(3ossl) OpenSSL PKCS12\_GET\_FRIENDLYNAME(3ossl)

#### NAME

PKCS12\_get\_friendlyname - Retrieve the friendlyname attribute from a PKCS#12 safeBag

#### SYNOPSIS

```
#include <openssl/pkcs12.h>
```

```
char *PKCS12_get_friendlyname(PKCS12_SAFEBAG *bag);
```

#### DESCRIPTION

PKCS12\_get\_friendlyname() retrieves a UTF-8 string representation of the PKCS#9 friendlyName attribute for a PKCS#12 safeBag item.

bag is the PKCS12\_SAFEBAG to retrieve the attribute from.

#### RETURN VALUES

A UTF-8 string, or NULL if the attribute was either not present or an error occurred.

The returned string is allocated by OpenSSL and should be freed by the user.

#### SEE ALSO

PKCS12\_add\_friendlyname\_asc(3)

#### COPYRIGHT

Copyright 2019 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13   PKCS12\_GET\_FRIENDLYNAME(3ossl)