



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'PKCS12_init.3ossl'

\$ man PKCS12_init.3ossl

PKCS12_INIT(3ossl) OpenSSL PKCS12_INIT(3ossl)

NAME

PKCS12_init, PKCS12_init_ex - Create a new empty PKCS#12 structure

SYNOPSIS

```
#include <openssl/pkcs12.h>
```

```
PKCS12 *PKCS12_init(int mode);
```

```
PKCS12 *PKCS12_init_ex(int mode, OSSL_LIB_CTX *ctx, const char *propq);
```

DESCRIPTION

PKCS12_init() creates an empty PKCS#12 structure. Any PKCS#7 authSafes added to this structure are enclosed first within a single PKCS#7 contentInfo of type mode. Currently the only supported type is NID_pkcs7_data.

PKCS12_init_ex() creates an empty PKCS#12 structure and assigns the

supplied ctx and propq to be used to select algorithm implementations for operations performed on the PKCS12 object.

RETURN VALUES

PKCS12_init() and PKCS12_init_ex() return a valid PKCS12 structure or NULL if an error occurred.

SEE ALSO

d2i_PKCS12(3), PKCS12_create(3), passphrase-encoding(7)

HISTORY

PKCS12_init_ex() was added in OpenSSL 3.0.

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 PKCS12_INIT(3ossl)