



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'RSA_free.3ossl'

\$ man RSA_free.3ossl

RSA_NEW(3ossl) OpenSSL RSA_NEW(3ossl)

NAME

RSA_new, RSA_free - allocate and free RSA objects

SYNOPSIS

```
#include <openssl/rsa.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
RSA *RSA_new(void);
```

```
void RSA_free(RSA *rsa);
```

DESCRIPTION

RSA_new() allocates and initializes an RSA structure. It is equivalent

to calling `RSA_new_method(NULL)`.

`RSA_free()` frees the RSA structure and its components. The key is erased before the memory is returned to the system. If `rsa` is `NULL` nothing is done.

RETURN VALUES

If the allocation fails, `RSA_new()` returns `NULL` and sets an error code that can be obtained by `ERR_get_error(3)`. Otherwise it returns a pointer to the newly allocated structure.

`RSA_free()` returns no value.

SEE ALSO

`ERR_get_error(3)`, `RSA_generate_key(3)`, `RSA_new_method(3)`

HISTORY

All functions described here were deprecated in OpenSSL 3.0. For replacement see `EVP_PKEY-RSA(7)`.

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.