



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'RSA_print.3ossl'

\$ man RSA_print.3ossl

RSA_PRINT(3ossl) OpenSSL RSA_PRINT(3ossl)

NAME

RSA_print, RSA_print_fp, DSAParams_print, DSAParams_print_fp,
DSA_print, DSA_print_fp, DHparams_print, DHparams_print_fp - print
cryptographic parameters

SYNOPSIS

```
#include <openssl/rsa.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
int RSA_print(BIO *bp, const RSA *x, int offset);  
int RSA_print_fp(FILE *fp, const RSA *x, int offset);
```

```
#include <openssl/dsa.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
int DSAParams_print(BIO *bp, const DSA *x);  
int DSAParams_print_fp(FILE *fp, const DSA *x);
```

```
int DSA_print(BIO *bp, const DSA *x, int offset);
int DSA_print_fp(FILE *fp, const DSA *x, int offset);
#include <openssl/dh.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining `OPENSSL_API_COMPAT` with a suitable version value, see `openssl_user_macros(7)`:

```
int DHparams_print(BIO *bp, DH *x);
int DHparams_print_fp(FILE *fp, const DH *x);
```

DESCRIPTION

All of the functions described on this page are deprecated.

Applications should instead use `EVP_PKEY_print_params(3)` and `EVP_PKEY_print_private(3)`.

A human-readable hexadecimal output of the components of the RSA key, DSA parameters or key or DH parameters is printed to `bp` or `fp`.

The output lines are indented by offset spaces.

RETURN VALUES

`DSAParams_print()`, `DSAParams_print_fp()`, `DSA_print()`, and `DSA_print_fp()` return 1 for success and 0 or a negative value for failure.

`DHparams_print()` and `DHparams_print_fp()` return 1 on success, 0 on error.

SEE ALSO

L<`EVP_PKEY_print_params(3)`>,
L<`EVP_PKEY_print_private(3)`>,
L<`BN_bn2bin(3)`>

HISTORY

All of these functions were deprecated in OpenSSL 3.0.

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at

<<https://www.openssl.org/source/license.html>>.

