



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'RSA_verify.3ossl'

\$ man RSA_verify.3ossl

RSA_SIGN(3ossl) OpenSSL RSA_SIGN(3ossl)

NAME

RSA_sign, RSA_verify - RSA signatures

SYNOPSIS

```
#include <openssl/rsa.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
int RSA_sign(int type, const unsigned char *m, unsigned int m_len,  
             unsigned char *sigret, unsigned int *siglen, RSA *rsa);
```

```
int RSA_verify(int type, const unsigned char *m, unsigned int m_len,  
              unsigned char *sigbuf, unsigned int siglen, RSA *rsa);
```

DESCRIPTION

All of the functions described on this page are deprecated.

Applications should instead use `EVP_PKEY_sign_init(3)`, `EVP_PKEY_sign(3)`, `EVP_PKEY_verify_init(3)` and `EVP_PKEY_verify(3)`.

`RSA_sign()` signs the message digest `m` of size `m_len` using the private key `rsa` using RSASSA-PKCS1-v1_5 as specified in RFC 3447. It stores the signature in `sigret` and the signature size in `siglen`. `sigret` must point to `RSA_size(rsa)` bytes of memory. Note that PKCS #1 adds meta-data, placing limits on the size of the key that can be used. See `RSA_private_encrypt(3)` for lower-level operations.

`type` denotes the message digest algorithm that was used to generate `m`.

If `type` is `NID_md5_sha1`, an SSL signature (MD5 and SHA1 message digests with PKCS #1 padding and no algorithm identifier) is created.

`RSA_verify()` verifies that the signature `sigbuf` of size `siglen` matches a given message digest `m` of size `m_len`. `type` denotes the message digest algorithm that was used to generate the signature. `rsa` is the signer's public key.

RETURN VALUES

`RSA_sign()` returns 1 on success. `RSA_verify()` returns 1 on successful verification.

The error codes can be obtained by `ERR_get_error(3)`.

CONFORMING TO

SSL, PKCS #1 v2.0

SEE ALSO

`ERR_get_error(3)`, `RSA_private_encrypt(3)`, `RSA_public_decrypt(3)`

HISTORY

All of these functions were deprecated in OpenSSL 3.0.

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 RSA_SIGN(3ossl)