



***Rocky Enterprise Linux 9.2 Manual Pages on command 'SRP\_VBASE\_add0\_user.3ossl'***

***\$ man SRP\_VBASE\_add0\_user.3ossl***

SRP\_VBASE\_NEW(3ossl)            OpenSSL            SRP\_VBASE\_NEW(3ossl)

NAME

SRP\_VBASE\_new, SRP\_VBASE\_free, SRP\_VBASE\_init, SRP\_VBASE\_add0\_user,  
SRP\_VBASE\_get1\_by\_user, SRP\_VBASE\_get\_by\_user - Functions to create and  
manage a stack of SRP user verifier information

SYNOPSIS

```
#include <openssl/srp.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can  
be hidden entirely by defining OPENSSL\_API\_COMPAT with a suitable  
version value, see openssl\_user\_macros(7):

```
SRP_VBASE *SRP_VBASE_new(char *seed_key);  
void SRP_VBASE_free(SRP_VBASE *vb);  
int SRP_VBASE_init(SRP_VBASE *vb, char *verifier_file);  
int SRP_VBASE_add0_user(SRP_VBASE *vb, SRP_user_pwd *user_pwd);  
SRP_user_pwd *SRP_VBASE_get1_by_user(SRP_VBASE *vb, char *username);  
SRP_user_pwd *SRP_VBASE_get_by_user(SRP_VBASE *vb, char *username);
```

DESCRIPTION

All of the functions described on this page are deprecated. There are

no available replacement functions at this time.

The `SRP_VBASE_new()` function allocates a structure to store server side SRP verifier information. If `seed_key` is not NULL a copy is stored and used to generate dummy parameters for users that are not found by `SRP_VBASE_get1_by_user()`. This allows the server to hide the fact that it doesn't have a verifier for a particular username, as described in section 2.5.1.3 'Unknown SRP' of RFC 5054. The seed string should contain random NUL terminated binary data (therefore the random data should not contain NUL bytes!).

The `SRP_VBASE_free()` function frees up the `vb` structure. If `vb` is NULL, nothing is done.

The `SRP_VBASE_init()` function parses the information in a verifier file and populates the `vb` structure. The verifier file is a text file containing multiple entries, whose format is: `flag base64(verifier) base64(salt) username gNid userinfo(optional)` where the flag can be 'V' (valid) or 'R' (revoked). Note that the base64 encoding used here is non-standard so it is recommended to use `openssl-srp(1)` to generate this file.

The `SRP_VBASE_add0_user()` function adds the `user_pwd` verifier information to the `vb` structure. See `SRP_user_pwd_new(3)` to create and populate this record. The library takes ownership of `user_pwd`, it should not be freed by the caller.

The `SRP_VBASE_get1_by_user()` function returns the password info for the user whose username matches `username`. It replaces the deprecated `SRP_VBASE_get_by_user()`. If no matching user is found but a `seed_key` and default `gN` parameters have been set, dummy authentication information is generated from the `seed_key`, allowing the server to hide the fact that it doesn't have a verifier for a particular username.

When using SRP as a TLS authentication mechanism, this will cause the handshake to proceed normally but the first client will be rejected with a "bad\_record\_mac" alert, as if the password was incorrect. If no matching user is found and the `seed_key` is not set, NULL is returned.

Ownership of the returned pointer is released to the caller, it must be

freed with `SRP_user_pwd_free()`.

## RETURN VALUES

`SRP_VBASE_init()` returns `SRP_NO_ERROR` (0) on success and a positive value on failure. The error codes are `SRP_ERR_OPEN_FILE` if the file could not be opened, `SRP_ERR_VBASE_INCOMPLETE_FILE` if the file could not be parsed, `SRP_ERR_MEMORY` on memory allocation failure and `SRP_ERR_VBASE_BN_LIB` for invalid decoded parameter values.

`SRP_VBASE_add0_user()` returns 1 on success and 0 on failure.

## SEE ALSO

`openssl-srp(1)`, `SRP_create_verifier(3)`, `SRP_user_pwd_new(3)`,  
`SSL_CTX_set_srp_password(3)`

## HISTORY

The `SRP_VBASE_add0_user()` function was added in OpenSSL 3.0.

All other functions were added in OpenSSL 1.0.1.

All of these functions were deprecated in OpenSSL 3.0.

## COPYRIGHT

Copyright 2018-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use

this file except in compliance with the License. You can obtain a copy

in the file `LICENSE` in the source distribution or at

[<https://www.openssl.org/source/license.html>](https://www.openssl.org/source/license.html).

3.0.7                    2023-07-13            `SRP_VBASE_NEW(3openssl)`