



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL_CTX_set_default_ctlog_list_file.3ossl'

```
$ man SSL_CTX_set_default_ctlog_list_file.3ossl
```

```
SSL_CTX_SET_CTLOG_LIST_FILE(3ossl) OpenSSL SSL_CTX_SET_CTLOG_LIST_FILE(3ossl)
```

NAME

SSL_CTX_set_default_ctlog_list_file, SSL_CTX_set_ctlog_list_file - load
a Certificate Transparency log list from a file

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
int SSL_CTX_set_default_ctlog_list_file(SSL_CTX *ctx);
```

```
int SSL_CTX_set_ctlog_list_file(SSL_CTX *ctx, const char *path);
```

DESCRIPTION

SSL_CTX_set_default_ctlog_list_file() loads a list of Certificate
Transparency (CT) logs from the default file location,
"ct_log_list.cnf", found in the directory where OpenSSL is installed.

SSL_CTX_set_ctlog_list_file() loads a list of CT logs from a specific

path. See CTLOG_STORE_new(3) for the file format.

NOTES

These functions will not clear the existing CT log list - it will be appended to. To replace the existing list, use SSL_CTX_set0_ctlog_store(3) first.

If an error occurs whilst parsing a particular log entry in the file, that log entry will be skipped.

RETURN VALUES

SSL_CTX_set_default_ctlog_list_file() and SSL_CTX_set_ctlog_list_file() return 1 if the log list is successfully loaded, and 0 if an error occurs. In the case of an error, the log list may have been partially loaded.

SEE ALSO

ssl(7), SSL_CTX_set_ct_validation_callback(3), CTLOG_STORE_new(3)

COPYRIGHT

Copyright 2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13SSL_CTX_SET_CTLOG_LIST_FILE(3ossl)