



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL\_SESSION\_get\_compress\_id.3ossl'***

***\$ man SSL\_SESSION\_get\_compress\_id.3ossl***

SSL\_SESSION\_GET\_COMPRESS\_ID(3ossl) OpenSSL SSL\_SESSION\_GET\_COMPRESS\_ID(3ossl)

### NAME

SSL\_SESSION\_get\_compress\_id - get details about the compression associated with a session

### SYNOPSIS

```
#include <openssl/ssl.h>
```

```
unsigned int SSL_SESSION_get_compress_id(const SSL_SESSION *s);
```

### DESCRIPTION

If compression has been negotiated for an ssl session then `SSL_SESSION_get_compress_id()` will return the id for the compression method or 0 otherwise. The only built-in supported compression method is zlib which has an id of 1.

### RETURN VALUES

SSL\_SESSION\_get\_compress\_id() returns the id of the compression method or 0 if none.

#### SEE ALSO

ssl(7)

#### COPYRIGHT

Copyright 2017 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13SSL\_SESSION\_GET\_COMPRESS\_ID(3ossl)