



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL_SESSION_set_protocol_version.3ossl'

```
$ man SSL_SESSION_set_protocol_version.3ossl
```

```
SSL_SESSION_GET_PROTOCOL_VERSION(3osOpeSSL_SESSION_GET_PROTOCOL_VERSION(3ossl)
```

NAME

SSL_SESSION_get_protocol_version, SSL_SESSION_set_protocol_version -
get and set the session protocol version

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
int SSL_SESSION_get_protocol_version(const SSL_SESSION *s);
```

```
int SSL_SESSION_set_protocol_version(SSL_SESSION *s, int version);
```

DESCRIPTION

SSL_SESSION_get_protocol_version() returns the protocol version number used by session s.

SSL_SESSION_set_protocol_version() sets the protocol version associated with the SSL_SESSION object s to the value version. This value should

be a version constant such as `TLS1_3_VERSION` etc. For example, this could be used to set up a session based PSK (see `SSL_CTX_set_psk_use_session_callback(3)`).

RETURN VALUES

`SSL_SESSION_get_protocol_version()` returns a number indicating the protocol version used for the session; this number matches the constants e.g. `TLS1_VERSION`, `TLS1_2_VERSION` or `TLS1_3_VERSION`.

Note that the `SSL_SESSION_get_protocol_version()` function does not perform a null check on the provided session s pointer.

`SSL_SESSION_set_protocol_version()` returns 1 on success or 0 on failure.

SEE ALSO

`ssl(7)`, `SSL_CTX_set_psk_use_session_callback(3)`

HISTORY

The `SSL_SESSION_get_protocol_version()` function was added in OpenSSL 1.1.0. The `SSL_SESSION_set_protocol_version()` function was added in OpenSSL 1.1.1.

COPYRIGHT

Copyright 2001-2018 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.