



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL_get0_peer_scts.3ossl'

\$ man SSL_get0_peer_scts.3ossl

SSL_GET0_PEER_SCTS(3ossl) OpenSSL SSL_GET0_PEER_SCTS(3ossl)

NAME

SSL_get0_peer_scts - get SCTs received

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
const STACK_OF(SCT) *SSL_get0_peer_scts(SSL *s);
```

DESCRIPTION

SSL_get0_peer_scts() returns the signed certificate timestamps (SCTs) that have been received. If this is the first time that this function has been called for a given SSL instance, it will examine the TLS extensions, OCSP response and the peer's certificate for SCTs. Future calls will return the same SCTs.

RESTRICTIONS

If no Certificate Transparency validation callback has been set (using `SSL_CTX_set_ct_validation_callback` or `SSL_set_ct_validation_callback`), this function is not guaranteed to return all of the SCTs that the peer is capable of sending.

RETURN VALUES

`SSL_get0_peer_scts()` returns a list of SCTs found, or NULL if an error occurs.

SEE ALSO

`ssl(7)`, `SSL_CTX_set_ct_validation_callback(3)`

COPYRIGHT

Copyright 2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at [<https://www.openssl.org/source/license.html>](https://www.openssl.org/source/license.html).

3.0.7 2023-07-13 SSL_GET0_PEER_SCTS(3ossl)