



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL_get_SSL_CTX.3ossl'

\$ man SSL_get_SSL_CTX.3ossl

SSL_GET_SSL_CTX(3ossl) OpenSSL SSL_GET_SSL_CTX(3ossl)

NAME

SSL_get_SSL_CTX - get the SSL_CTX from which an SSL is created

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
SSL_CTX *SSL_get_SSL_CTX(const SSL *ssl);
```

DESCRIPTION

SSL_get_SSL_CTX() returns a pointer to the SSL_CTX object, from which ssl was created with SSL_new(3).

RETURN VALUES

The pointer to the SSL_CTX object is returned.

SEE ALSO

ssl(7), SSL_new(3)

COPYRIGHT

Copyright 2001-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 SSL_GET_SSL_CTX(3ossl)