



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL_get_wfd.3ossl'

\$ man SSL_get_wfd.3ossl

SSL_GET_FD(3ossl) OpenSSL SSL_GET_FD(3ossl)

NAME

SSL_get_fd, SSL_get_rfd, SSL_get_wfd - get file descriptor linked to an SSL object

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
int SSL_get_fd(const SSL *ssl);  
int SSL_get_rfd(const SSL *ssl);  
int SSL_get_wfd(const SSL *ssl);
```

DESCRIPTION

SSL_get_fd() returns the file descriptor which is linked to ssl.
SSL_get_rfd() and SSL_get_wfd() return the file descriptors for the read or the write channel, which can be different. If the read and the write channel are different, SSL_get_fd() will return the file

descriptor of the read channel.

RETURN VALUES

The following return values can occur:

-1 The operation failed, because the underlying BIO is not of the correct type (suitable for file descriptors).

>=0 The file descriptor linked to ssl.

SEE ALSO

SSL_set_fd(3), ssl(7) , bio(7)

COPYRIGHT

Copyright 2000-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 SSL_GET_FD(3ossl)