



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'SSL\_set\_ecdh\_auto.3ossl'***

***\$ man SSL\_set\_ecdh\_auto.3ossl***

SSL\_CTX\_SET\_TMP\_ECDH(3ossl)    OpenSSL    SSL\_CTX\_SET\_TMP\_ECDH(3ossl)

#### NAME

SSL\_CTX\_set\_tmp\_ecdh, SSL\_set\_tmp\_ecdh, SSL\_CTX\_set\_ecdh\_auto,  
SSL\_set\_ecdh\_auto - handle ECDH keys for ephemeral key exchange

#### SYNOPSIS

```
#include <openssl/ssl.h>
```

```
long SSL_CTX_set_tmp_ecdh(SSL_CTX *ctx, const EC_KEY *ecdh);
```

```
long SSL_set_tmp_ecdh(SSL *ssl, const EC_KEY *ecdh);
```

```
long SSL_CTX_set_ecdh_auto(SSL_CTX *ctx, int state);
```

```
long SSL_set_ecdh_auto(SSL *ssl, int state);
```

#### DESCRIPTION

SSL\_CTX\_set\_tmp\_ecdh() sets ECDH parameters to be used to be ecdh. The key is inherited by all ssl objects created from ctx. This macro is

deprecated in favor of `SSL_CTX_set1_groups(3)`.

`SSL_set_tmp_ecdh()` sets the parameters only for `ssl`. This macro is deprecated in favor of `SSL_set1_groups(3)`.

`SSL_CTX_set_ecdh_auto()` and `SSL_set_ecdh_auto()` are deprecated and have no effect.

## RETURN VALUES

`SSL_CTX_set_tmp_ecdh()` and `SSL_set_tmp_ecdh()` return 1 on success and 0 on failure.

## SEE ALSO

`ssl(7)`, `SSL_CTX_set1_curves(3)`, `SSL_CTX_set_cipher_list(3)`,  
`SSL_CTX_set_options(3)`, `SSL_CTX_set_tmp_dh_callback(3)`,  
`openssl-ciphers(1)`, `openssl-ecparam(1)`

## COPYRIGHT

Copyright 2018 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13    `SSL_CTX_SET_TMP_ECDH(3ossl)`