



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'X509\_CRL\_load\_http.3ossl'***

***\$ man X509\_CRL\_load\_http.3ossl***

X509\_LOAD\_HTTP(3ossl)          OpenSSL          X509\_LOAD\_HTTP(3ossl)

#### NAME

X509\_load\_http, X509\_http\_nbio, X509\_CRL\_load\_http, X509\_CRL\_http\_nbio

- certificate and CRL loading functions

#### SYNOPSIS

```
#include <openssl/x509.h>
```

```
X509 *X509_load_http(const char *url, BIO *bio, BIO *rbio, int timeout);
```

```
X509_CRL *X509_CRL_load_http(const char *url, BIO *bio, BIO *rbio, int timeout);
```

The following macros have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL\_API\_COMPAT with a suitable version value, see openssl\_user\_macros(7):

```
#define X509_http_nbio(rctx, pcert)
```

```
#define X509_CRL_http_nbio(rctx, pcr)
```

## DESCRIPTION

`X509_load_http()` and `X509_CRL_load_http()` loads a certificate or a CRL, respectively, in ASN.1 format using HTTP from the given url.

If `bio` is given and `rbio` is NULL then this BIO is used instead of an internal one for connecting, writing the request, and reading the response. If both `bio` and `rbio` are given (which may be memory BIOs, for instance) then no explicit connection is attempted, `bio` is used for writing the request, and `rbio` for reading the response.

If the `timeout` parameter is  $> 0$  this indicates the maximum number of seconds to wait until the transfer is complete. A value of 0 enables waiting indefinitely, while a value  $< 0$  immediately leads to a timeout condition.

`X509_http_nbio()` and `X509_CRL_http_nbio()` are macros for backward compatibility that have the same effect as the functions above but with infinite timeout and without the possibility to specify custom BIOs.

## RETURN VALUES

On success the function yield the loaded value, else NULL. Error conditions include connection/transfer timeout, parse errors, etc.

## SEE ALSO

`OSSL_HTTP_get(3)`

## HISTORY

`X509_load_http()` and `X509_CRL_load_http()` were added in OpenSSL 3.0.

`X509_http_nbio()` and `X509_CRL_http_nbio()` were deprecated in OpenSSL 3.0.

Copyright 2019-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13            X509\_LOAD\_HTTP(3ossl)