



*Full credit is given to the above companies including the OS that this PDF file was generated!*

***Rocky Enterprise Linux 9.2 Manual Pages on command 'X509\_EXTENSION\_create\_by\_OBJ.3oss1'***

***\$ man X509\_EXTENSION\_create\_by\_OBJ.3oss1***

X509\_EXTENSION\_SET\_OBJECT(3oss1) OpenSSL X509\_EXTENSION\_SET\_OBJECT(3oss1)

NAME

X509\_EXTENSION\_set\_object, X509\_EXTENSION\_set\_critical,  
X509\_EXTENSION\_set\_data, X509\_EXTENSION\_create\_by\_NID,  
X509\_EXTENSION\_create\_by\_OBJ, X509\_EXTENSION\_get\_object,  
X509\_EXTENSION\_get\_critical, X509\_EXTENSION\_get\_data - extension  
utility functions

SYNOPSIS

```
int X509_EXTENSION_set_object(X509_EXTENSION *ex, const ASN1_OBJECT *obj);
int X509_EXTENSION_set_critical(X509_EXTENSION *ex, int crit);
int X509_EXTENSION_set_data(X509_EXTENSION *ex, ASN1_OCTET_STRING *data);
X509_EXTENSION *X509_EXTENSION_create_by_NID(X509_EXTENSION **ex,
int nid, int crit,
ASN1_OCTET_STRING *data);
X509_EXTENSION *X509_EXTENSION_create_by_OBJ(X509_EXTENSION **ex,
const ASN1_OBJECT *obj, int crit,
ASN1_OCTET_STRING *data);
ASN1_OBJECT *X509_EXTENSION_get_object(X509_EXTENSION *ex);
```

```
int X509_EXTENSION_get_critical(const X509_EXTENSION *ex);
ASN1_OCTET_STRING *X509_EXTENSION_get_data(X509_EXTENSION *ne);
```

## DESCRIPTION

X509\_EXTENSION\_set\_object() sets the extension type of ex to obj. The obj pointer is duplicated internally so obj should be freed up after use.

X509\_EXTENSION\_set\_critical() sets the criticality of ex to crit. If crit is zero the extension is non-critical otherwise it is critical.

X509\_EXTENSION\_set\_data() sets the data in extension ex to data. The data pointer is duplicated internally.

X509\_EXTENSION\_create\_by\_NID() creates an extension of type nid, criticality crit using data data. The created extension is returned and written to \*ex reusing or allocating a new extension if necessary so \*ex should either be NULL or a valid X509\_EXTENSION structure it must not be an uninitialised pointer.

X509\_EXTENSION\_create\_by\_OBJ() is identical to X509\_EXTENSION\_create\_by\_NID() except it creates an extension using obj instead of a NID.

X509\_EXTENSION\_get\_object() returns the extension type of ex as an ASN1\_OBJECT pointer. The returned pointer is an internal value which must not be freed up.

X509\_EXTENSION\_get\_critical() returns the criticality of extension ex it returns 1 for critical and 0 for non-critical.

X509\_EXTENSION\_get\_data() returns the data of extension ex. The returned pointer is an internal value which must not be freed up.

## NOTES

These functions manipulate the contents of an extension directly. Most applications will want to parse or encode and add an extension: they should use the extension encode and decode functions instead such as X509\_add1\_ext\_i2d() and X509\_get\_ext\_d2i().

The data associated with an extension is the extension encoding in an ASN1\_OCTET\_STRING structure.

## RETURN VALUES

X509\_EXTENSION\_set\_object() X509\_EXTENSION\_set\_critical() and X509\_EXTENSION\_set\_data() return 1 for success and 0 for failure. X509\_EXTENSION\_create\_by\_NID() and X509\_EXTENSION\_create\_by\_OBJ() return an X509\_EXTENSION pointer or NULL if an error occurs. X509\_EXTENSION\_get\_object() returns an ASN1\_OBJECT pointer. X509\_EXTENSION\_get\_critical() returns 0 for non-critical and 1 for critical. X509\_EXTENSION\_get\_data() returns an ASN1\_OCTET\_STRING pointer.

#### SEE ALSO

X509V3\_get\_d2i(3)

#### COPYRIGHT

Copyright 2015-2016 The OpenSSL Project Authors. All Rights Reserved. Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13 X509\_EXTENSION\_SET\_OBJECT(3openssl)