



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'X509_SIG_get0.3oss1'

\$ man X509_SIG_get0.3oss1

X509_SIG_GET0(3oss1) OpenSSL X509_SIG_GET0(3oss1)

NAME

X509_SIG_get0, X509_SIG_getm - DigestInfo functions

SYNOPSIS

```
#include <openssl/x509.h>
```

```
void X509_SIG_get0(const X509_SIG *sig, const X509_ALGOR **palg,  
                  const ASN1_OCTET_STRING **pdigest);
```

```
void X509_SIG_getm(X509_SIG *sig, X509_ALGOR **palg,  
                  ASN1_OCTET_STRING **pdigest);
```

DESCRIPTION

X509_SIG_get0() returns pointers to the algorithm identifier and digest value in sig. X509_SIG_getm() is identical to X509_SIG_get0() except the pointers returned are not constant and can be modified: for example to initialise them.

RETURN VALUES

X509_SIG_get0() and X509_SIG_getm() return no values.

SEE ALSO

d2i_X509(3)

COPYRIGHT

Copyright 2002-2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 X509_SIG_GET0(3ossl)