



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'X509_add_certs.3ossl'

\$ man X509_add_certs.3ossl

X509_ADD_CERT(3ossl) OpenSSL X509_ADD_CERT(3ossl)

NAME

X509_add_cert, X509_add_certs - X509 certificate list addition

functions

SYNOPSIS

```
#include <openssl/x509.h>
```

```
int X509_add_cert(STACK_OF(X509) *sk, X509 *cert, int flags);
```

```
int X509_add_certs(STACK_OF(X509) *sk, STACK_OF(X509) *certs, int flags);
```

DESCRIPTION

X509_add_cert() adds a certificate cert to the given list sk.

X509_add_certs() adds a list of certificate certs to the given list sk.

The certs argument may be NULL, which implies no effect. It does not

modify the list certs but in case the X509_ADD_FLAG_UP_REF flag

(described below) is set the reference counters of those of its members

added to sk are increased.

Both these functions have a flags parameter, which is used to control

details of the operation.

The value X509_ADD_FLAG_DEFAULT, which equals 0, means no special

semantics.

If `X509_ADD_FLAG_UP_REF` is set then the reference counts of those certificates added successfully are increased.

If `X509_ADD_FLAG_PREPEND` is set then the certificates are prepended to `sk`. By default they are appended to `sk`. In both cases the original order of the added certificates is preserved.

If `X509_ADD_FLAG_NO_DUP` is set then certificates already contained in `sk`, which is determined using `X509_cmp(3)`, are ignored.

If `X509_ADD_FLAG_NO_SS` is set then certificates that are marked self-signed, which is determined using `X509_self_signed(3)`, are ignored.

RETURN VALUES

Both functions return 1 for success and 0 for failure.

NOTES

If `X509_add_certs()` is used with the flags `X509_ADD_FLAG_NO_DUP` or `X509_ADD_FLAG_NO_SS` it is advisable to use also `X509_ADD_FLAG_UP_REF` because otherwise likely not for all members of the certs list the ownership is transferred to the list of certificates `sk`.

Care should also be taken in case the certs argument equals `sk`.

SEE ALSO

`X509_cmp(3)` `X509_self_signed(3)`

HISTORY

The functions `X509_add_cert()` and `X509_add_certs()` were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2019-2020 The OpenSSL Project Authors. All Rights Reserved.
Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 X509_ADD_CERT(3openssl)