



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'X509\_cmp\_current\_time.3ossl'***

***\$ man X509\_cmp\_current\_time.3ossl***

X509\_CMP\_TIME(3ossl)            OpenSSL            X509\_CMP\_TIME(3ossl)

#### NAME

X509\_cmp\_time, X509\_cmp\_current\_time, X509\_cmp\_timeframe,  
X509\_time\_adj, X509\_time\_adj\_ex, X509\_gmtime\_adj - X509 time functions

#### SYNOPSIS

```
int X509_cmp_time(const ASN1_TIME *asn1_time, time_t *in_tm);
int X509_cmp_current_time(const ASN1_TIME *asn1_time);
int X509_cmp_timeframe(const X509_VERIFY_PARAM *vpm,
                        const ASN1_TIME *start, const ASN1_TIME *end);
ASN1_TIME *X509_time_adj(ASN1_TIME *asn1_time, long offset_sec, time_t *in_tm);
ASN1_TIME *X509_time_adj_ex(ASN1_TIME *asn1_time, int offset_day, long
                             offset_sec, time_t *in_tm);
ASN1_TIME *X509_gmtime_adj(ASN1_TIME *asn1_time, long offset_sec);
```

#### DESCRIPTION

X509\_cmp\_time() compares the ASN1\_TIME in `asn1_time` with the time in `<in_tm>`.

X509\_cmp\_current\_time() compares the ASN1\_TIME in `asn1_time` with the current time, expressed as `time_t`.

X509\_cmp\_timeframe() compares the given time period with the reference time included in the verification parameters vpm if they are not NULL and contain X509\_V\_FLAG\_USE\_CHECK\_TIME; else the current time is used as reference time.

X509\_time\_adj\_ex() sets the ASN1\_TIME structure asn1\_time to the time offset\_day and offset\_sec after in\_tm.

X509\_time\_adj() sets the ASN1\_TIME structure asn1\_time to the time offset\_sec after in\_tm. This method can only handle second offsets up to the capacity of long, so the newer X509\_time\_adj\_ex() API should be preferred.

In both methods, if asn1\_time is NULL, a new ASN1\_TIME structure is allocated and returned.

In all methods, if in\_tm is NULL, the current time, expressed as time\_t, is used.

asn1\_time must satisfy the ASN1\_TIME format mandated by RFC 5280, i.e., its format must be either YYMMDDHHMMSSZ or YYYYMMDDHHMMSSZ.

X509\_gmtime\_adj() sets the ASN1\_TIME structure asn1\_time to the time offset\_sec after the current time. It is equivalent to calling X509\_time\_adj() with the last parameter as NULL.

## BUGS

Unlike many standard comparison functions, X509\_cmp\_time() and X509\_cmp\_current\_time() return 0 on error.

## RETURN VALUES

X509\_cmp\_time() and X509\_cmp\_current\_time() return -1 if asn1\_time is earlier than, or equal to, in\_tm (resp. current time), and 1 otherwise.

These methods return 0 on error.

X509\_cmp\_timeframe() returns 0 if vpm is not NULL and the verification parameters do not contain X509\_V\_FLAG\_USE\_CHECK\_TIME but do contain X509\_V\_FLAG\_NO\_CHECK\_TIME. Otherwise it returns 1 if the end time is not NULL and the reference time (which has determined as stated above) is past the end time, -1 if the start time is not NULL and the reference time is before, else 0 to indicate that the reference time is in range (implying that the end time is not before the start time if

both are present).

X509\_time\_adj(), X509\_time\_adj\_ex() and X509\_gmtime\_adj() return a pointer to the updated ASN1\_TIME structure, and NULL on error.

## HISTORY

X509\_cmp\_timeframe() was added in OpenSSL 3.0.

## COPYRIGHT

Copyright 2017-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use

this file except in compliance with the License. You can obtain a copy

in the file LICENSE in the source distribution or at

<<https://www.openssl.org/source/license.html>>.

3.0.7                    2023-07-13            X509\_CMP\_TIME(3ossl)