



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'X509\_get0\_uids.3ossl'***

***\$ man X509\_get0\_uids.3ossl***

X509\_GET0\_UIDS(3ossl)      OpenSSL      X509\_GET0\_UIDS(3ossl)

#### NAME

X509\_get0\_uids - get certificate unique identifiers

#### SYNOPSIS

```
#include <openssl/x509.h>
```

```
void X509_get0_uids(const X509 *x, const ASN1_BIT_STRING **piuid,  
                  const ASN1_BIT_STRING **psuid);
```

#### DESCRIPTION

X509\_get0\_uids() sets \*piuid and \*psuid to the issuer and subject unique identifiers of certificate x or NULL if the fields are not present.

#### NOTES

The issuer and subject unique identifier fields are very rarely

encountered in practice outside test cases.

## RETURN VALUES

X509\_get0\_uids() does not return a value.

## SEE ALSO

d2i\_X509(3), ERR\_get\_error(3), X509\_CRL\_get0\_by\_serial(3),  
X509\_get0\_signature(3), X509\_get\_ext\_d2i(3),  
X509\_get\_extension\_flags(3), X509\_get\_pubkey(3),  
X509\_get\_subject\_name(3), X509\_get\_version(3),  
X509\_NAME\_add\_entry\_by\_txt(3), X509\_NAME\_ENTRY\_get\_object(3),  
X509\_NAME\_get\_index\_by\_NID(3), X509\_NAME\_print\_ex(3), X509\_new(3),  
X509\_sign(3), X509V3\_get\_d2i(3), X509\_verify\_cert(3)

## COPYRIGHT

Copyright 2015-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use  
this file except in compliance with the License. You can obtain a copy  
in the file LICENSE in the source distribution or at  
<<https://www.openssl.org/source/license.html>>.

3.0.7                    2023-07-13            X509\_GET0\_UIDS(3openssl)