



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'X509_new_ex.3ossl'

\$ man X509_new_ex.3ossl

X509_NEW(3ossl) OpenSSL X509_NEW(3ossl)

NAME

X509_new, X509_new_ex, X509_free, X509_up_ref, X509_chain_up_ref - X509 certificate ASN1 allocation functions

SYNOPSIS

```
#include <openssl/x509.h>

X509 *X509_new(void);
X509 *X509_new_ex(OSSL_LIB_CTX *libctx, const char *propq);
void X509_free(X509 *a);
int X509_up_ref(X509 *a);
STACK_OF(X509) *X509_chain_up_ref(STACK_OF(X509) *x);
```

DESCRIPTION

The X509 ASN1 allocation routines, allocate and free an X509 structure, which represents an X509 certificate.

X509_new_ex() allocates and initializes a X509 structure with a library context of libctx, property query of propq and a reference count of 1. Many X509 functions such as X509_check_purpose(), and X509_verify() use this library context to select which providers supply the fetched algorithms (SHA1 is used internally). This created X509 object can then be used when loading binary data using d2i_X509().

X509_new() is similar to X509_new_ex() but sets the library context and property query to NULL. This results in the default (NULL) library context being used for any X509 operations requiring algorithm fetches.

X509_free() decrements the reference count of X509 structure a and frees it up if the reference count is zero. If a is NULL nothing is done.

X509_up_ref() increments the reference count of a.

X509_chain_up_ref() increases the reference count of all certificates in chain x and returns a copy of the stack, or an empty stack if a is NULL.

NOTES

The function X509_up_ref() is useful if a certificate structure is being used by several different operations each of which will free it up after use: this avoids the need to duplicate the entire certificate structure.

The function X509_chain_up_ref() doesn't just up the reference count of each certificate. It also returns a copy of the stack, using sk_X509_dup(), but it serves a similar purpose: the returned chain persists after the original has been freed.

RETURN VALUES

If the allocation fails, `X509_new()` returns `NULL` and sets an error code that can be obtained by `ERR_get_error(3)`. Otherwise it returns a pointer to the newly allocated structure.

`X509_up_ref()` returns 1 for success and 0 for failure.

`X509_chain_up_ref()` returns a copy of the stack or `NULL` if an error occurred.

SEE ALSO

`d2i_X509(3)`, `ERR_get_error(3)`, `X509_CRL_get0_by_serial(3)`,
`X509_get0_signature(3)`, `X509_get_ext_d2i(3)`,
`X509_get_extension_flags(3)`, `X509_get_pubkey(3)`,
`X509_get_subject_name(3)`, `X509_get_version(3)`,
`X509_NAME_add_entry_by_txt(3)`, `X509_NAME_ENTRY_get_object(3)`,
`X509_NAME_get_index_by_NID(3)`, `X509_NAME_print_ex(3)`, `X509_sign(3)`,
`X509V3_get_d2i(3)`, `X509_verify_cert(3)`

HISTORY

The function `X509_new_ex()` was added in OpenSSL 3.0.

COPYRIGHT

Copyright 2002-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.