



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'b2i_PVK_bio.3ossl'

\$ man b2i_PVK_bio.3ossl

B2I_PVK_BIO_EX(3ossl) OpenSSL B2I_PVK_BIO_EX(3ossl)

NAME

b2i_PVK_bio, b2i_PVK_bio_ex, i2b_PVK_bio, i2b_PVK_bio_ex - Decode and encode functions for reading and writing MSBLOB format private keys

SYNOPSIS

```
#include <openssl/pem.h>
```

```
EVP_PKEY *b2i_PVK_bio(BIO *in, pem_password_cb *cb, void *u);
```

```
EVP_PKEY *b2i_PVK_bio_ex(BIO *in, pem_password_cb *cb, void *u,
```

```
          OSSL_LIB_CTX *libctx, const char *propq);
```

```
int i2b_PVK_bio(BIO *out, const EVP_PKEY *pk, int encllevel,
```

```
          pem_password_cb *cb, void *u);
```

```
int i2b_PVK_bio_ex(BIO *out, const EVP_PKEY *pk, int encllevel,
```

```
          pem_password_cb *cb, void *u,
```

```
          OSSL_LIB_CTX *libctx, const char *propq);
```

DESCRIPTION

`b2i_PVK_bio_ex()` decodes a private key of MSBLOB format read from a BIO. It attempts to automatically determine the key type. If the key is encrypted then `cb` is called with the user data `u` in order to obtain a password to decrypt the key. The supplied library context `libctx` and property query string `propq` are used in any decrypt operation.

`b2i_PVK_bio()` does the same as `b2i_PVK_bio_ex()` except that the default library context and property query string are used.

`i2b_PVK_bio_ex()` encodes `pk` using MSBLOB format. If `enclevel` is 1 then a password obtained via `pem_password_cb` is used to encrypt the private key. If `enclevel` is 0 then no encryption is applied. The user data in `u` is passed to the password callback. The supplied library context `libctx` and property query string `propq` are used in any decrypt operation.

`i2b_PVK_bio()` does the same as `i2b_PVK_bio_ex()` except that the default library context and property query string are used.

RETURN VALUES

The `b2i_PVK_bio()` and `b2i_PVK_bio_ex()` functions return a valid `EVP_KEY` structure or `NULL` if an error occurs. The error code can be obtained by calling `ERR_get_error(3)`.

`i2b_PVK_bio()` and `i2b_PVK_bio_ex()` return the number of bytes successfully encoded or a negative value if an error occurs. The error code can be obtained by calling `ERR_get_error(3)`.

SEE ALSO

`crypto(7)`, `d2i_PKCS8PrivateKey_bio(3)`

HISTORY

b2i_PVK_bio_ex() and i2b_PVK_bio_ex() were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 B2I_PVK_BIO_EX(3ossl)