

Full credit is given to the above companies including the OS that this PDF file was generated!

# Rocky Enterprise Linux 9.2 Manual Pages on command 'buildah-manifest-push.1'

# *\$ man buildah-manifest-push.1*

buildah-manifest-push(1) General Commands Manual buildah-manifest-push(1)

## NAME

buildah-manifest-push - Push a manifest list or image index to a reg?

istry.

## SYNOPSIS

buildah manifest push [options...] listNameOrIndexName transport:de?

tails

## DESCRIPTION

Pushes a manifest list or image index to a registry.

#### **RETURN VALUE**

The list image's ID and the digest of the image's manifest.

#### OPTIONS

--all

Push the images mentioned in the manifest list or image index, in addi?

tion to the list or index itself.

--authfile path

Path of the authentication file. Default is \${XDG\_RUNTIME\_DIR}/contain?

ers/auth.json, which is set using buildah login. If the authorization

state is not found there, \$HOME/.docker/config.json is checked, which is set using docker login.

--cert-dir path

Use certificates at path (\*.crt, \*.cert, \*.key) to connect to the reg?

istry. The default certificates directory is /etc/containers/certs.d.

--creds creds

The [username[:password]] to use to authenticate with the registry if required. If one or both values are not supplied, a command line prompt will appear and the value can be entered. The password is en? tered without echo.

--digestfile Digestfile

After copying the image, write the digest of the resulting image to the

file.

--format, -f

Manifest list type (oci or v2s2) to use when pushing the list (default

is oci).

--quiet, -q

Don't output progress information when pushing lists.

--remove-signatures

Don't copy signatures when pushing images.

--rm

Delete the manifest list or image index from local storage if pushing

succeeds.

--sign-by fingerprint

Sign the pushed images using the GPG key that matches the specified

fingerprint.

--tls-verify bool-value

Require HTTPS and verification of certificates when talking to con?

tainer registries (defaults to true). TLS verification cannot be used

when talking to an insecure registry.

#### EXAMPLE

buildah manifest push mylist:v1.11 registry.example.org/mylist:v1.11

buildah(1), buildah-login(1), buildah-manifest(1), buildah-manifestcreate(1), buildah-manifest-add(1), buildah-manifest-remove(1), buil? dah-manifest-annotate(1), buildah-manifest-inspect(1), buildah-rmi(1), docker-login(1)

buildah September 2019 buildah-manifest-push(1)