



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'bundle-init.1'

\$ man bundle-init.1

BUNDLE-INIT(1) BUNDLE-INIT(1)

NAME

bundle-init - Generates a Gemfile into the current working directory

SYNOPSIS

bundle init [--gemspec=FILE]

DESCRIPTION

Init generates a default [Gemfile(5)][Gemfile(5)] in the current work? ing directory. When adding a [Gemfile(5)][Gemfile(5)] to a gem with a gemspec, the --gemspec option will automatically add each dependency listed in the gemspec file to the newly created [Gemfile(5)][Gem? file(5)].

OPTIONS

--gemspec

Use the specified .gemspec to create the [Gemfile(5)][Gem? file(5)]

FILES

Included in the default [Gemfile(5)][Gemfile(5)] generated is the line

```
# frozen_string_literal: true. This is a magic comment supported for
```

the first time in Ruby 2.3. The presence of this line results in all string literals in the file being implicitly frozen.

SEE ALSO

[Gemfile\(5\)](https://bundler.io/man/gemfile.5.html) <https://bundler.io/man/gemfile.5.html>

December 2021

BUNDLE-INIT(1)