



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'containers-registries.conf.d.5'

\$ man containers-registries.conf.d.5

CONTAINERS-REGISTRIES.CONF.D(5)File Formats ManuCONTAINERS-REGISTRIES.CONF.D(5)

Valentin Rothberg Mar 2020

NAME

containers-registries.conf.d - directory for drop-in registries.conf
files

DESCRIPTION

CONTAINERS-REGISTRIES.CONF.D is a system-wide directory for drop-in configuration files in the containers-registries.conf(5) format.

By default, the directory is located at /etc/containers/reg?
istries.conf.d.

CONFIGURATION PRECEDENCE

Once the main configuration at /etc/containers/registries.conf is loaded, the files in /etc/containers/registries.conf.d are loaded in

alpha-numerical order. Then the conf files in \$HOME/.config/containers/registries.conf.d are loaded in alpha-numerical order, if they exist. If the \$HOME/.config/containers/registries.conf is loaded, only the conf files under \$HOME/.config/containers/registries.conf.d are loaded in alpha-numerical order. Specified fields in a conf file will overwrite any previous setting. Note that only files with the .conf suffix are loaded, other files and sub-directories are ignored.

For instance, setting the unqualified-search-registries in /etc/containers/registries.conf.d/myregistries.conf will overwrite previous settings in /etc/containers/registries.conf. The [[registry]] tables merged by overwriting existing items if the prefixes are identical while new ones are added.

All drop-in configuration files must be specified in the version 2 of the containers-registries.conf(5) format.

SEE ALSO

[containers-registries.conf\(5\)](#)

HISTORY

Mar 2020, Originally compiled by Valentin Rothberg rothberg@redhat.com
?mailto:rothberg@redhat.com?

CONTAINERS-REGISTRIES.CONF.D(5)