



Rocky Enterprise Linux 9.2 Manual Pages on command 'cups-genppd.8'

\$ man cups-genppd.8

CUPS-GENPPD(8) Gutenprint Manual Pages CUPS-GENPPD(8)

NAME

cups-genppd - generate Gutenprint PPD files for use with CUPS

SYNOPSIS

cups-genppd [-c localedir] [-l locale] [-p prefix] [-q] [-v] model1

[model2, ...modeln]

cups-genppd -L [-c localedir]

cups-genppd -M [-v]

cups-genppd -h

cups-genppd -V

DESCRIPTION

cups-genppd generates Gutenprint PPD files for use with CUPS. The de?

fault behavior is to output PPD files for all models of printer that

the Gutenprint printer driver library supports. You may restrict the

models by listing either the driver names or the full names of the

printers you wish to generate PPD files for after any options. Addi?

tionally, the PPD files may be localised, that is, translated, to use

your native language rather than US English. There are commands to

find out what printer models and languages are supported.

EXAMPLES

```
cups-genppd -v bjc-6200 'Epson Stylus Photo 1280' 'HP DeskJet 850C'
```

verbosely generate three PPD files, listing the driver name in the first case, and the full name in the second.

```
LANG=de_DE genppd -p ppd -c /usr/share/locale
```

generate PPDs for all available models, in directory `ppd` using the locale data found under `/usr/share/locale`. The language to use is taken from the environment (`de_DE`).

```
cups-genppd -L -c /usr/local/share/locale
```

list available languages using the locale data found under `/usr/local/share/locale`.

```
cups-genppd -M -v
```

list available drivers, with long model descriptions

COMMANDS

- h show a help message
- L list available translations (message catalogs). If a locale is used for which there is not a corresponding translation, then then US English will be used.
- M list available printer models. By default, only driver names are listed; if verbose mode is used, the full model name will also be printed
- V show version information and defaults

The default behavior is to output PPDs if no command is given.

OPTIONS

- c localedir
use localedir as the base directory for locale data
- l locale
output PPDs translated with messages for locale. Note that locale must be a locale as shown by `locale -a`. For example, the `de` translation is used by the `de_DE` locale; `de` alone will not work.
- p prefix

output PPDs in directory prefix. Directories are not recur?

sively created.

-q Quiet mode.

-v Verbose mode.

models a list of printer models, either the driver or quoted full name.

SEE ALSO

CUPS Software Administrators Manual, <http://localhost:631/documentation.html>

COPYRIGHT

Copyright ? 1992-2002 Michael Sweet (mike@easysw.com)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License, version 2, as published by the Free Software Foundation.

This manual page was written by Roger Leigh (rleigh@debian.org).

Version 5.3.4

06 Dec 2020

CUPS-GENPPD(8)