



Rocky Enterprise Linux 9.2 Manual Pages on command 'cupsctl.8'

\$ man cupsctl.8

cupsctl(8) OpenPrinting cupsctl(8)

NAME

cupsctl - configure cupsd.conf options

SYNOPSIS

```
cupsctl [ -h server[:port] ] [ -E ] [ -U username ] [ --[no-]debug-log?  
ging ] [ --[no-]remote-admin ] [ --[no-]remote-any ] [  
--[no-]share-printers ] [ --[no-]user-cancel-any ] [ name=value ]
```

DESCRIPTION

cupsctl updates or queries the cupsd.conf file for a server. When no changes are requested, the current configuration values are written to the standard output in the format "name=value", one per line.

OPTIONS

The following options are recognized:

-E Enables encryption on the connection to the scheduler.

-U username

Specifies an alternate username to use when authenticating with the scheduler.

-h server[:port]

Specifies the server address. Note: This option must occur before all others.

--[no-]debug-logging

Enables (disables) debug logging to the error_log file.

--[no-]remote-admin

Enables (disables) remote administration.

--[no-]remote-any

Enables (disables) printing from any address, e.g., the Internet.

--[no-]share-printers

Enables (disables) sharing of local printers with other computers.

--[no-]user-cancel-any

Allows (prevents) users to cancel jobs owned by others.

EXAMPLES

Display the current settings:

```
cupsctl
```

Enable debug logging:

```
cupsctl --debug-logging
```

Get the current debug logging state:

```
cupswctl | grep '^_debug_logging' | awk -F= '{print $2}'
```

Disable printer sharing:

```
cupswctl --no-share-printers
```

KNOWN ISSUES

You cannot set the Listen or Port directives using cupswctl.

SEE ALSO

cupswd.conf(5), cupswd(8),

CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright ? 2007-2019 by Apple Inc.

2022-05-02

CUPS

cupswctl(8)