



Rocky Enterprise Linux 9.2 Manual Pages on command 'dbus-monitor.1'

\$ man dbus-monitor.1

DBUS-MONITOR(1) User Commands DBUS-MONITOR(1)

NAME

dbus-monitor - debug probe to print message bus messages

SYNOPSIS

```
dbus-monitor [--system | --session | --address ADDRESS] [--profile |  
--monitor | --pcap | --binary] [watch expressions]
```

DESCRIPTION

The dbus-monitor command is used to monitor messages going through a D-Bus message bus. See <http://www.freedesktop.org/software/dbus/> for more information about the big picture.

There are two well-known message buses: the systemwide message bus (installed on many systems as the "messagebus" service) and the per-user-login-session message bus (started each time a user logs in).

The --system and --session options direct dbus-monitor to monitor the system or session buses respectively. If neither is specified, dbus-monitor monitors the session bus.

dbus-monitor has two different text output modes: the 'classic'-style monitoring mode, and profiling mode. The profiling format is a compact

format with a single line per message and microsecond-resolution timing information. The `--profile` and `--monitor` options select the profiling and monitoring output format respectively.

`dbus-monitor` also has two binary output modes. The binary mode, selected by `--binary`, outputs the entire binary message stream (without the initial authentication handshake). The PCAP mode, selected by `--pcap`, adds a PCAP file header to the beginning of the output, and prepends a PCAP message header to each message; this produces a binary file that can be read by, for instance, Wireshark.

If no mode is specified, `dbus-monitor` uses the monitoring output format.

In order to get `dbus-monitor` to see the messages you are interested in, you should specify a set of watch expressions as you would expect to be passed to the `dbus_bus_add_match` function.

The message bus configuration may keep `dbus-monitor` from seeing all messages, especially if you run the monitor as a non-root user.

OPTIONS

`--system`

Monitor the system message bus.

`--session`

Monitor the session message bus. (This is the default.)

`--address ADDRESS`

Monitor an arbitrary message bus given at ADDRESS.

`--profile`

Use the profiling output format.

`--monitor`

Use the monitoring output format. (This is the default.)

EXAMPLE

Here is an example of using `dbus-monitor` to watch for the gnome typing monitor to say things

```
dbus-monitor "type='signal',sender='org.gnome.TypingMonitor',interface='org.gnome.TypingMonitor'"
```

AUTHOR

`dbus-monitor` was written by Philip Blundell. The profiling output mode

was added by Olli Salli.

BUGS

Please send bug reports to the D-Bus mailing list or bug tracker, see

<http://www.freedesktop.org/software/dbus/>

D-Bus 1.12.20 06/12/2023 DBUS-MONITOR(1)