



*Full credit is given to the above companies including the OS that this PDF file was generated!*

*Rocky Enterprise Linux 9.2 Manual Pages on command 'fcntl.2'*

**\$ man fcntl.2**

FCNTL(2) Linux Programmer's Manual FCNTL(2)

NAME

## fcntl - manipulate file descriptor

## SYNOPSIS

```
#include <unistd.h>  
  
#include <fcntl.h>  
  
int fcntl(int fd, int cm
```

## DESCRIPTION

fcntl() performs one of the operations described below on the open file descriptor fd. The operation is determined by cmd.

fcntl() can take an optional third argument. Whether or not this argument is required is determined by cmd. The required argument type is indicated in parentheses after each cmd name (in most cases, the required type is int, and we identify the argument using the name arg), or void is specified if the argument is not required.

Certain of the operations below are supported only since a particular Linux kernel version. The preferred method of checking whether the host kernel supports a particular operation is to invoke `fcntl()` with

the desired cmd value and then test whether the call failed with EIN?

VAL, indicating that the kernel does not recognize this value.

Duplicating a file descriptor

**F\_DUPFD (int)**

Duplicate the file descriptor fd using the lowest-numbered available file descriptor greater than or equal to arg. This is different from dup2(2), which uses exactly the file descriptor specified.

On success, the new file descriptor is returned.

See dup(2) for further details.

**F\_DUPFD\_CLOEXEC (int; since Linux 2.6.24)**

As for F\_DUPFD, but additionally set the close-on-exec flag for the duplicate file descriptor. Specifying this flag permits a program to avoid an additional fcntl() F\_SETFD operation to set the FD\_CLOEXEC flag. For an explanation of why this flag is useful, see the description of O\_CLOEXEC in open(2).

File descriptor flags

The following commands manipulate the flags associated with a file descriptor. Currently, only one such flag is defined: FD\_CLOEXEC, the close-on-exec flag. If the FD\_CLOEXEC bit is set, the file descriptor will automatically be closed during a successful execve(2). (If the execve(2) fails, the file descriptor is left open.) If the FD\_CLOEXEC bit is not set, the file descriptor will remain open across an execve(2).

**F\_GETFD (void)**

Return (as the function result) the file descriptor flags; arg is ignored.

**F\_SETFD (int)**

Set the file descriptor flags to the value specified by arg.

In multithreaded programs, using fcntl() F\_SETFD to set the close-on-exec flag at the same time as another thread performs a fork(2) plus execve(2) is vulnerable to a race condition that may unintentionally leak the file descriptor to the program executed in the child process.

See the discussion of the O\_CLOEXEC flag in open(2) for details and a remedy to the problem.

## File status flags

Each open file description has certain associated status flags, initialized by open(2) and possibly modified by fcntl(). Duplicated file descriptors (made with dup(2), fcntl(F\_DUPFD), fork(2), etc.) refer to the same open file description, and thus share the same file status flags.

The file status flags and their semantics are described in open(2).

### F\_GETFL (void)

Return (as the function result) the file access mode and the file status flags; arg is ignored.

### F\_SETFL (int)

Set the file status flags to the value specified by arg. File access mode (O\_RDONLY, O\_WRONLY, O\_RDWR) and file creation flags (i.e., O\_CREAT, O\_EXCL, O\_NOCTTY, O\_TRUNC) in arg are ignored.

On Linux, this command can change only the O\_APPEND, O\_ASYNC, O\_DIRECT, O\_NOATIME, and O\_NONBLOCK flags. It is not possible to change the O\_DSYNC and O\_SYNC flags; see BUGS, below.

## Advisory record locking

Linux implements traditional ("process-associated") UNIX record locks, as standardized by POSIX. For a Linux-specific alternative with better semantics, see the discussion of open file description locks below.

F\_SETLK, F\_SETLKW, and F\_GETLK are used to acquire, release, and test for the existence of record locks (also known as byte-range, file-segment, or file-region locks). The third argument, lock, is a pointer to a structure that has at least the following fields (in unspecified order).

```
struct flock {  
    ...  
    short l_type; /* Type of lock: F_RDLCK,  
                   F_WRLCK, F_UNLCK */  
    short l_whence; /* How to interpret l_start:  
                   SEEK_SET, SEEK_CUR, SEEK_END */  
    long l_start; /* Starting offset */  
    long l_end; /* Ending offset */  
    pid_t l_pid; /* Process ID */  
};
```

```

SEEK_SET, SEEK_CUR, SEEK_END */

off_t l_start; /* Starting offset for lock */

off_t l_len; /* Number of bytes to lock */

pid_t l_pid; /* PID of process blocking our lock

(set by F_GETLK and F_OFD_GETLK) */

...
};


```

The l\_whence, l\_start, and l\_len fields of this structure specify the range of bytes we wish to lock. Bytes past the end of the file may be locked, but not bytes before the start of the file.

l\_start is the starting offset for the lock, and is interpreted relative to either: the start of the file (if l\_whence is SEEK\_SET); the current file offset (if l\_whence is SEEK\_CUR); or the end of the file (if l\_whence is SEEK\_END). In the final two cases, l\_start can be a negative number provided the offset does not lie before the start of the file.

l\_len specifies the number of bytes to be locked. If l\_len is positive, then the range to be locked covers bytes l\_start up to and including l\_start+l\_len-1. Specifying 0 for l\_len has the special meaning: lock all bytes starting at the location specified by l\_whence and l\_start through to the end of file, no matter how large the file grows. POSIX.1-2001 allows (but does not require) an implementation to support a negative l\_len value; if l\_len is negative, the interval described by lock covers bytes l\_start+l\_len up to and including l\_start-1. This is supported by Linux since kernel versions 2.4.21 and 2.5.49.

The l\_type field can be used to place a read (F\_RDLCK) or a write (F\_WRLCK) lock on a file. Any number of processes may hold a read lock (shared lock) on a file region, but only one process may hold a write lock (exclusive lock). An exclusive lock excludes all other locks, both shared and exclusive. A single process can hold only one type of lock on a file region; if a new lock is applied to an already-locked region, then the existing lock is converted to the new lock type.

(Such conversions may involve splitting, shrinking, or coalescing with

an existing lock if the byte range specified by the new lock does not precisely coincide with the range of the existing lock.)

#### F\_SETLK (struct flock \*)

Acquire a lock (when l\_type is F\_RDLCK or F\_WRLCK) or release a lock (when l\_type is F\_UNLCK) on the bytes specified by the l\_whence, l\_start, and l\_len fields of lock. If a conflicting lock is held by another process, this call returns -1 and sets errno to EACCES or EAGAIN. (The error returned in this case differs across implementations, so POSIX requires a portable application to check for both errors.)

#### F\_SETLKW (struct flock \*)

As for F\_SETLK, but if a conflicting lock is held on the file, then wait for that lock to be released. If a signal is caught while waiting, then the call is interrupted and (after the signal handler has returned) returns immediately (with return value -1 and errno set to EINTR; see signal(7)).

#### F\_GETLK (struct flock \*)

On input to this call, lock describes a lock we would like to place on the file. If the lock could be placed, fcntl() does not actually place it, but returns F\_UNLCK in the l\_type field of lock and leaves the other fields of the structure unchanged. If one or more incompatible locks would prevent this lock being placed, then fcntl() returns details about one of those locks in the l\_type, l\_whence, l\_start, and l\_len fields of lock. If the conflicting lock is a traditional (process-associated) record lock, then the l\_pid field is set to the PID of the process holding that lock. If the conflicting lock is an open file description lock, then l\_pid is set to -1. Note that the returned information may already be out of date by the time the caller inspects it.

In order to place a read lock, fd must be open for reading. In order to place a write lock, fd must be open for writing. To place both types of lock, open a file read-write.

When placing locks with `F_SETLK`, the kernel detects deadlocks, whereby two or more processes have their lock requests mutually blocked by locks held by the other processes. For example, suppose process A holds a write lock on byte 100 of a file, and process B holds a write lock on byte 200. If each process then attempts to lock the byte at? ready locked by the other process using `F_SETLK`, then, without dead? lock detection, both processes would remain blocked indefinitely. When the kernel detects such deadlocks, it causes one of the blocking lock requests to immediately fail with the error `EDEADLK`; an application that encounters such an error should release some of its locks to allow other applications to proceed before attempting to regain the locks that it requires. Circular deadlocks involving more than two processes are also detected. Note, however, that there are limitations to the ker? nel's deadlock-detection algorithm; see [BUGS](#).

As well as being removed by an explicit `F_UNLCK`, record locks are automatically released when the process terminates.

Record locks are not inherited by a child created via `fork(2)`, but are preserved across an `execve(2)`.

Because of the buffering performed by the `stdio(3)` library, the use of record locking with routines in that package should be avoided; use `read(2)` and `write(2)` instead.

The record locks described above are associated with the process (un? like the open file description locks described below). This has some unfortunate consequences:

\* If a process closes any file descriptor referring to a file, then all of the process's locks on that file are released, regardless of the file descriptor(s) on which the locks were obtained. This is bad: it means that a process can lose its locks on a file such as `/etc/passwd` or `/etc/mtab` when for some reason a library function de? cides to open, read, and close the same file.

\* The threads in a process share locks. In other words, a multi? threaded program can't use record locking to ensure that threads don't simultaneously access the same region of a file.

Open file description locks solve both of these problems.

#### Open file description locks (non-POSIX)

Open file description locks are advisory byte-range locks whose operation is in most respects identical to the traditional record locks described above. This lock type is Linux-specific, and available since Linux 3.15. (There is a proposal with the Austin Group to include this lock type in the next revision of POSIX.1.) For an explanation of open file descriptions, see `open(2)`.

The principal difference between the two lock types is that whereas traditional record locks are associated with a process, open file description locks are associated with the open file description on which they are acquired, much like locks acquired with `flock(2)`. Consequently (and unlike traditional advisory record locks), open file description locks are inherited across `fork(2)` (and `clone(2)` with `CLONE_FILES`), and are only automatically released on the last close of the open file description, instead of being released on any close of the file.

Conflicting lock combinations (i.e., a read lock and a write lock or two write locks) where one lock is an open file description lock and the other is a traditional record lock conflict even when they are acquired by the same process on the same file descriptor.

Open file description locks placed via the same open file description (i.e., via the same file descriptor, or via a duplicate of the file descriptor created by `fork(2)`, `dup(2)`, `fcntl()` `F_DUPFD`, and so on) are always compatible: if a new lock is placed on an already locked region, then the existing lock is converted to the new lock type. (Such conversions may result in splitting, shrinking, or coalescing with an existing lock as discussed above.)

On the other hand, open file description locks may conflict with each other when they are acquired via different open file descriptions. Thus, the threads in a multithreaded program can use open file description locks to synchronize access to a file region by having each thread perform its own `open(2)` on the file and applying locks via the result?

ing file descriptor.

As with traditional advisory locks, the third argument to `fcntl()`, `lock`, is a pointer to an `flock` structure. By contrast with traditional record locks, the `l_pid` field of that structure must be set to zero when using the commands described below.

The commands for working with open file description locks are analogous to those used with traditional locks:

#### `F_OFD_SETLK` (struct `flock` \*)

Acquire an open file description lock (when `l_type` is `F_RDLCK` or `F_WRLCK`) or release an open file description lock (when `l_type` is `F_UNLCK`) on the bytes specified by the `l_whence`, `l_start`, and `l_len` fields of `lock`. If a conflicting lock is held by another process, this call returns `-1` and sets `errno` to `EAGAIN`.

#### `F_OFD_SETLKW` (struct `flock` \*)

As for `F_OFD_SETLK`, but if a conflicting lock is held on the file, then wait for that lock to be released. If a signal is caught while waiting, then the call is interrupted and (after the signal handler has returned) returns immediately (with `re?` turn value `-1` and `errno` set to `EINTR`; see `signal(7)`).

#### `F_OFD_GETLK` (struct `flock` \*)

On input to this call, `lock` describes an open file description lock we would like to place on the file. If the lock could be placed, `fcntl()` does not actually place it, but returns `F_UNLCK` in the `l_type` field of `lock` and leaves the other fields of the structure unchanged. If one or more incompatible locks would prevent this lock being placed, then details about one of these locks are returned via `lock`, as described above for `F_GETLK`.

In the current implementation, no deadlock detection is performed for open file description locks. (This contrasts with process-associated record locks, for which the kernel does perform deadlock detection.)

### Mandatory locking

Warning: the Linux implementation of mandatory locking is unreliable.

See `BUGS` below. Because of these bugs, and the fact that the feature

is believed to be little used, since Linux 4.5, mandatory locking has been made an optional feature, governed by a configuration option (CON? FIG\_MANDATORY\_FILE\_LOCKING). This is an initial step toward removing this feature completely.

By default, both traditional (process-associated) and open file description record locks are advisory. Advisory locks are not enforced and are useful only between cooperating processes.

Both lock types can also be mandatory. Mandatory locks are enforced for all processes. If a process tries to perform an incompatible access (e.g., read(2) or write(2)) on a file region that has an incompatible mandatory lock, then the result depends upon whether the O\_NONBLOCK flag is enabled for its open file description. If the O\_NONBLOCK flag is not enabled, then the system call is blocked until the lock is removed or converted to a mode that is compatible with the access. If the O\_NONBLOCK flag is enabled, then the system call fails with the error EAGAIN.

To make use of mandatory locks, mandatory locking must be enabled both on the filesystem that contains the file to be locked, and on the file itself. Mandatory locking is enabled on a filesystem using the "-o mand" option to mount(8), or the MS\_MANDLOCK flag for mount(2). Mandatory locking is enabled on a file by disabling group execute permission on the file and enabling the set-group-ID permission bit (see chmod(1) and chmod(2)).

Mandatory locking is not specified by POSIX. Some other systems also support mandatory locking, although the details of how to enable it vary across systems.

### Lost locks

When an advisory lock is obtained on a networked filesystem such as NFS it is possible that the lock might get lost. This may happen due to administrative action on the server, or due to a network partition (i.e., loss of network connectivity with the server) which lasts long enough for the server to assume that the client is no longer functioning.

When the filesystem determines that a lock has been lost, future read(2) or write(2) requests may fail with the error EIO. This error will persist until the lock is removed or the file descriptor is closed. Since Linux 3.12, this happens at least for NFSv4 (including all minor versions).

Some versions of UNIX send a signal (SIGLOST) in this circumstance. Linux does not define this signal, and does not provide any asynchronous notification of lost locks.

#### Managing signals

F\_GETOWN, F\_SETOWN, F\_GETOWN\_EX, F\_SETOWN\_EX, F\_GETSIG, and F\_SETSIG are used to manage I/O availability signals:

##### F\_GETOWN (void)

Return (as the function result) the process ID or process group ID currently receiving SIGIO and SIGURG signals for events on file descriptor fd. Process IDs are returned as positive values; process group IDs are returned as negative values (but see BUGS below). arg is ignored.

##### F\_SETOWN (int)

Set the process ID or process group ID that will receive SIGIO and SIGURG signals for events on the file descriptor fd. The target process or process group ID is specified in arg. A process ID is specified as a positive value; a process group ID is specified as a negative value. Most commonly, the calling process specifies itself as the owner (that is, arg is specified as getpid(2)).

As well as setting the file descriptor owner, one must also enable generation of signals on the file descriptor. This is done by using the fcntl() F\_SETFL command to set the O\_ASYNC file status flag on the file descriptor. Subsequently, a SIGIO signal is sent whenever input or output becomes possible on the file descriptor. The fcntl() F\_SETSIG command can be used to obtain delivery of a signal other than SIGIO.

Sending a signal to the owner process (group) specified by F\_SE?

TOWN is subject to the same permissions checks as are described for kill(2), where the sending process is the one that employs F\_SETOWN (but see BUGS below). If this permission check fails, then the signal is silently discarded. Note: The F\_SETOWN operation records the caller's credentials at the time of the fcntl() call, and it is these saved credentials that are used for the permission checks.

If the file descriptor fd refers to a socket, F\_SETOWN also selects the recipient of SIGURG signals that are delivered when out-of-band data arrives on that socket. (SIGURG is sent in any situation where select(2) would report the socket as having an "exceptional condition".)

The following was true in 2.6.x kernels up to and including kernel 2.6.11:

If a nonzero value is given to F\_SETSIG in a multi-threaded process running with a threading library that supports thread groups (e.g., NPTL), then a positive value given to F\_SETOWN has a different meaning: instead of being a process ID identifying a whole process, it is a thread ID identifying a specific thread within a process. Consequently, it may be necessary to pass F\_SETOWN the result of gettid(2) instead of getpid(2) to get sensible results when F\_SETSIG is used. (In current Linux threading implementations, a main thread's thread ID is the same as its process ID. This means that a single-threaded program can equally use gettid(2) or getpid(2) in this scenario.) Note, however, that the statements in this paragraph do not apply to the SIGURG signal generated for out-of-band data on a socket: this signal is always sent to either a process or a process group, depending on the value given to F\_SETOWN.

The above behavior was accidentally dropped in Linux 2.6.12, and won't be restored. From Linux 2.6.32 onward, use F\_SETOWN\_EX to

target SIGIO and SIGURG signals at a particular thread.

#### F\_GETOWN\_EX (struct f\_owner\_ex \*) (since Linux 2.6.32)

Return the current file descriptor owner settings as defined by a previous F\_SETOWN\_EX operation. The information is returned in the structure pointed to by arg, which has the following form:

```
struct f_owner_ex {  
    int type;  
    pid_t pid;  
};
```

The type field will have one of the values F\_OWNER\_TID, F\_OWNER\_PID, or F\_OWNER\_PGRP. The pid field is a positive integer representing a thread ID, process ID, or process group ID.

See F\_SETOWN\_EX for more details.

#### F\_SETOWN\_EX (struct f\_owner\_ex \*) (since Linux 2.6.32)

This operation performs a similar task to F\_SETOWN. It allows the caller to direct I/O availability signals to a specific thread, process, or process group. The caller specifies the target of signals via arg, which is a pointer to a f\_owner\_ex structure. The type field has one of the following values, which define how pid is interpreted:

##### F\_OWNER\_TID

Send the signal to the thread whose thread ID (the value returned by a call to clone(2) or gettid(2)) is specified in pid.

##### F\_OWNER\_PID

Send the signal to the process whose ID is specified in pid.

##### F\_OWNER\_PGRP

Send the signal to the process group whose ID is specified in pid. (Note that, unlike with F\_SETOWN, a process group ID is specified as a positive value here.)

#### F\_GETSIG (void)

Return (as the function result) the signal sent when input or output becomes possible. A value of zero means SIGIO is sent. Any other value (including SIGIO) is the signal sent instead, and in this case additional info is available to the signal handler if installed with SA\_SIGINFO. arg is ignored.

#### F\_SETSIG (int)

Set the signal sent when input or output becomes possible to the value given in arg. A value of zero means to send the default SIGIO signal. Any other value (including SIGIO) is the signal to send instead, and in this case additional info is available to the signal handler if installed with SA\_SIGINFO.

By using F\_SETSIG with a nonzero value, and setting SA\_SIGINFO for the signal handler (see `sigaction(2)`), extra information about I/O events is passed to the handler in a `siginfo_t` structure. If the `si_code` field indicates the source is `SI_SIGIO`, the `si_fd` field gives the file descriptor associated with the event. Otherwise, there is no indication which file descriptors are pending, and you should use the usual mechanisms (`select(2)`, `poll(2)`, `read(2)` with `O_NONBLOCK` set etc.) to determine which file descriptors are available for I/O.

Note that the file descriptor provided in `si_fd` is the one that was specified during the F\_SETSIG operation. This can lead to an unusual corner case. If the file descriptor is duplicated (`dup(2)` or similar), and the original file descriptor is closed, then I/O events will continue to be generated, but the `si_fd` field will contain the number of the now closed file descriptor.

By selecting a real time signal (value  $\geq$  `SIGRTMIN`), multiple I/O events may be queued using the same signal numbers. (Queuing is dependent on available memory.) Extra information is available if SA\_SIGINFO is set for the signal handler, as above. Note that Linux imposes a limit on the number of real-time signals that may be queued to a process (see `getrlimit(2)` and `sigional(7)`) and if this limit is reached, then the kernel reverts to

delivering SIGIO, and this signal is delivered to the entire process rather than to a specific thread.

Using these mechanisms, a program can implement fully asynchronous I/O without using select(2) or poll(2) most of the time.

The use of O\_ASYNC is specific to BSD and Linux. The only use of F\_GETOWN and F\_SETOWN specified in POSIX.1 is in conjunction with the use of the SIGURG signal on sockets. (POSIX does not specify the SIGIO signal.) F\_GETOWN\_EX, F\_SETOWN\_EX, F\_GETSIG, and F\_SETSIG are Linux-specific. POSIX has asynchronous I/O and the aio\_sigevent structure to achieve similar things; these are also available in Linux as part of the GNU C Library (Glibc).

## Leases

F\_SETLEASE and F\_GETLEASE (Linux 2.4 onward) are used to establish a new lease, and retrieve the current lease, on the open file description referred to by the file descriptor fd. A file lease provides a mechanism whereby the process holding the lease (the "lease holder") is notified (via delivery of a signal) when a process (the "lease breaker") tries to open(2) or truncate(2) the file referred to by that file descriptor.

### F\_SETLEASE (int)

Set or remove a file lease according to which of the following values is specified in the integer arg:

#### F\_RDLCK

Take out a read lease. This will cause the calling process to be notified when the file is opened for writing or is truncated. A read lease can be placed only on a file descriptor that is opened read-only.

#### F\_WRLCK

Take out a write lease. This will cause the caller to be notified when the file is opened for reading or writing or is truncated. A write lease may be placed on a file only if there are no other open file descriptors for the file.

## F\_UNLCK

Remove our lease from the file.

Leases are associated with an open file description (see open(2)).

This means that duplicate file descriptors (created by, for example, fork(2) or dup(2)) refer to the same lease, and this lease may be modified or released using any of these descriptors. Furthermore, the lease is released by either an explicit F\_UNLCK operation on any of these duplicate file descriptors, or when all such file descriptors have been closed.

Leases may be taken out only on regular files. An unprivileged process may take out a lease only on a file whose UID (owner) matches the filesystem UID of the process. A process with the CAPLEASE capability may take out leases on arbitrary files.

## F\_GETLEASE (void)

Indicates what type of lease is associated with the file descriptor fd by returning either F\_RDLCK, F\_WRLCK, or F\_UNLCK, indicating, respectively, a read lease, a write lease, or no lease. arg is ignored.

When a process (the "lease breaker") performs an open(2) or truncate(2) that conflicts with a lease established via F\_SETLEASE, the system call is blocked by the kernel and the kernel notifies the lease holder by sending it a signal (SIGIO by default). The lease holder should respond to receipt of this signal by doing whatever cleanup is required in preparation for the file to be accessed by another process (e.g., flushing cached buffers) and then either remove or downgrade its lease.

A lease is removed by performing an F\_SETLEASE command specifying arg as F\_UNLCK. If the lease holder currently holds a write lease on the file, and the lease breaker is opening the file for reading, then it is sufficient for the lease holder to downgrade the lease to a read lease.

This is done by performing an F\_SETLEASE command specifying arg as F\_RDLCK.

If the lease holder fails to downgrade or remove the lease within the number of seconds specified in /proc/sys/fs/lease-break-time, then the

kernel forcibly removes or downgrades the lease holder's lease.

Once a lease break has been initiated, F\_GETLEASE returns the target lease type (either F\_RDLCK or F\_UNLCK, depending on what would be compatible with the lease breaker) until the lease holder voluntarily downgrades or removes the lease or the kernel forcibly does so after the lease break timer expires.

Once the lease has been voluntarily or forcibly removed or downgraded, and assuming the lease breaker has not unblocked its system call, the kernel permits the lease breaker's system call to proceed.

If the lease breaker's blocked open(2) or truncate(2) is interrupted by a signal handler, then the system call fails with the error EINTR, but the other steps still occur as described above. If the lease breaker is killed by a signal while blocked in open(2) or truncate(2), then the other steps still occur as described above. If the lease breaker specifies the O\_NONBLOCK flag when calling open(2), then the call immediately fails with the error EWOULDBLOCK, but the other steps still occur as described above.

The default signal used to notify the lease holder is SIGIO, but this can be changed using the F\_SETSIG command to fcntl(). If a F\_SETSIG command is performed (even one specifying SIGIO), and the signal handler is established using SA\_SIGINFO, then the handler will receive a siginfo\_t structure as its second argument, and the si\_fd field of this argument will hold the file descriptor of the leased file that has been accessed by another process. (This is useful if the caller holds leases against multiple files.)

File and directory change notification (dnotify)

F\_NOTIFY (int)

(Linux 2.4 onward) Provide notification when the directory referred to by fd or any of the files that it contains is changed.

The events to be notified are specified in arg, which is a bit mask specified by ORing together zero or more of the following bits:

DN\_ACCESS

A file was accessed (read(2), pread(2), readv(2), and similar)

#### DN MODIFY

A file was modified (write(2), pwrite(2), writev(2), truncate(2), ftruncate(2), and similar).

#### DN CREATE

A file was created (open(2), creat(2), mknod(2), mkdir(2), link(2), symlink(2), rename(2) into this directory).

#### DN DELETE

A file was unlinked (unlink(2), rename(2) to another directory, rmdir(2)).

#### DN RENAME

A file was renamed within this directory (rename(2)).

#### DN ATTRIB

The attributes of a file were changed (chown(2), chmod(2), utime(2), utimensat(2), and similar).

(In order to obtain these definitions, the \_GNU\_SOURCE feature test macro must be defined before including any header files.)

Directory notifications are normally "one-shot", and the application must reregister to receive further notifications. Alteratively, if DN\_MULTISHOT is included in arg, then notification will remain in effect until explicitly removed.

A series of F\_NOTIFY requests is cumulative, with the events in arg being added to the set already monitored. To disable notification of all events, make an F\_NOTIFY call specifying arg as 0.

Notification occurs via delivery of a signal. The default signal is SIGIO, but this can be changed using the F\_SETSIG command to fcntl(). (Note that SIGIO is one of the nonqueuing standard signals; switching to the use of a real-time signal means that multiple notifications can be queued to the process.) In the latter case, the signal handler receives a siginfo\_t structure

as its second argument (if the handler was established using `SA_SIGINFO`) and the `si_fd` field of this structure contains the file descriptor which generated the notification (useful when establishing notification on multiple directories).

Especially when using `DN_MULTISHOT`, a real time signal should be used for notification, so that multiple notifications can be queued.

NOTE: New applications should use the `inotify` interface (available since kernel 2.6.13), which provides a much superior interface for obtaining notifications of filesystem events. See `inotify(7)`.

Changing the capacity of a pipe

`F_SETPIPE_SZ` (int; since Linux 2.6.35)

Change the capacity of the pipe referred to by `fd` to be at least `arg` bytes. An unprivileged process can adjust the pipe capacity to any value between the system page size and the limit defined in `/proc/sys/fs/pipe-max-size` (see `proc(5)`). Attempts to set the pipe capacity below the page size are silently rounded up to the page size. Attempts by an unprivileged process to set the pipe capacity above the limit in `/proc/sys/fs/pipe-max-size` yield the error `EPERM`; a privileged process (`CAP_SYS_RESOURCE`) can override the limit.

When allocating the buffer for the pipe, the kernel may use a capacity larger than `arg`, if that is convenient for the implementation. (In the current implementation, the allocation is the next higher power-of-two page-size multiple of the requested size.) The actual capacity (in bytes) that is set is returned as the function result.

Attempting to set the pipe capacity smaller than the amount of buffer space currently used to store data produces the error `EBUSY`.

Note that because of the way the pages of the pipe buffer are employed when data is written to the pipe, the number of bytes

that can be written may be less than the nominal size, depending on the size of the writes.

#### **F\_GETPIPE\_SZ (void; since Linux 2.6.35)**

Return (as the function result) the capacity of the pipe referred to by fd.

### **File Sealing**

File seals limit the set of allowed operations on a given file. For each seal that is set on a file, a specific set of operations will fail with EPERM on this file from now on. The file is said to be sealed. The default set of seals depends on the type of the underlying file and filesystem. For an overview of file sealing, a discussion of its purpose, and some code examples, see `memfd_create(2)`.

Currently, file seals can be applied only to a file descriptor returned by `memfd_create(2)` (if the `MFD_ALLOW_SEALING` was employed). On other filesystems, all `fcntl()` operations that operate on seals will return `EINVAL`.

Seals are a property of an inode. Thus, all open file descriptors referring to the same inode share the same set of seals. Furthermore, seals can never be removed, only added.

#### **F\_ADD\_SEALS (int; since Linux 3.17)**

Add the seals given in the bit-mask argument arg to the set of seals of the inode referred to by the file descriptor fd. Seals cannot be removed again. Once this call succeeds, the seals are enforced by the kernel immediately. If the current set of seals includes `F_SEAL_SEAL` (see below), then this call will be rejected with EPERM. Adding a seal that is already set is a no-op, in case `F_SEAL_SEAL` is not set already. In order to place a seal, the file descriptor fd must be writable.

#### **F\_GET\_SEALS (void; since Linux 3.17)**

Return (as the function result) the current set of seals of the inode referred to by fd. If no seals are set, 0 is returned. If the file does not support sealing, -1 is returned and errno is set to `EINVAL`.

The following seals are available:

#### F\_SEAL\_SEAL

If this seal is set, any further call to fcntl() with F\_ADD\_SEALS fails with the error EPERM. Therefore, this seal prevents any modifications to the set of seals itself. If the initial set of seals of a file includes F\_SEAL\_SEAL, then this effectively causes the set of seals to be constant and locked.

#### F\_SEAL\_SHRINK

If this seal is set, the file in question cannot be reduced in size. This affects open(2) with the O\_TRUNC flag as well as truncate(2) and ftruncate(2). Those calls fail with EPERM if you try to shrink the file in question. Increasing the file size is still possible.

#### F\_SEAL\_GROW

If this seal is set, the size of the file in question cannot be increased. This affects write(2) beyond the end of the file, truncate(2), ftruncate(2), and fallocate(2). These calls fail with EPERM if you use them to increase the file size. If you keep the size or shrink it, those calls still work as expected.

#### F\_SEAL\_WRITE

If this seal is set, you cannot modify the contents of the file. Note that shrinking or growing the size of the file is still possible and allowed. Thus, this seal is normally used in combination with one of the other seals. This seal affects write(2) and fallocate(2) (only in combination with the FAL? LOC\_FL\_PUNCH\_HOLE flag). Those calls fail with EPERM if this seal is set. Furthermore, trying to create new shared, writable memory-mappings via mmap(2) will also fail with EPERM.

Using the F\_ADD\_SEALS operation to set the F\_SEAL\_WRITE seal fails with EBUSY if any writable, shared mapping exists. Such mappings must be unmapped before you can add this seal. Furthermore, if there are any asynchronous I/O operations (io\_submitt(2)) pending on the file, all outstanding writes will be dis?

carded.

## F\_SEAL\_FUTURE\_WRITE (since Linux 5.1)

The effect of this seal is similar to F\_SEAL\_WRITE, but the contents of the file can still be modified via shared writable map? pings that were created prior to the seal being set. Any attempt to create a new writable mapping on the file via mmap(2) will fail with EPERM. Likewise, an attempt to write to the file via write(2) will fail with EPERM.

Using this seal, one process can create a memory buffer that it can continue to modify while sharing that buffer on a "read-only" basis with other processes.

## File read/write hints

Write lifetime hints can be used to inform the kernel about the relative expected lifetime of writes on a given inode or via a particular open file description. (See open(2) for an explanation of open file descriptions.) In this context, the term "write lifetime" means the expected time the data will live on media, before being overwritten or erased.

An application may use the different hint values specified below to separate writes into different write classes, so that multiple users or applications running on a single storage back-end can aggregate their I/O patterns in a consistent manner. However, there are no functional semantics implied by these flags, and different I/O classes can use the write lifetime hints in arbitrary ways, so long as the hints are used consistently.

The following operations can be applied to the file descriptor, fd:

### F\_GET\_RW\_HINT (uint64\_t \*; since Linux 4.13)

Returns the value of the read/write hint associated with the underlying inode referred to by fd.

### F\_SET\_RW\_HINT (uint64\_t \*; since Linux 4.13)

Sets the read/write hint value associated with the underlying inode referred to by fd. This hint persists until either it is explicitly modified or the underlying filesystem is unmounted.

## F\_GET\_FILE\_RW\_HINT (uint64\_t \*; since Linux 4.13)

Returns the value of the read/write hint associated with the open file description referred to by fd.

## F\_SET\_FILE\_RW\_HINT (uint64\_t \*; since Linux 4.13)

Sets the read/write hint value associated with the open file description referred to by fd.

If an open file description has not been assigned a read/write hint, then it shall use the value assigned to the inode, if any.

The following read/write hints are valid since Linux 4.13:

### RWH\_WRITE\_LIFE\_NOT\_SET

No specific hint has been set. This is the default value.

### RWH\_WRITE\_LIFE\_NONE

No specific write lifetime is associated with this file or inode.

### RWH\_WRITE\_LIFE\_SHORT

Data written to this inode or via this open file description is expected to have a short lifetime.

### RWH\_WRITE\_LIFE\_MEDIUM

Data written to this inode or via this open file description is expected to have a lifetime longer than data written with RWH\_WRITE\_LIFE\_SHORT.

### RWH\_WRITE\_LIFE\_LONG

Data written to this inode or via this open file description is expected to have a lifetime longer than data written with RWH\_WRITE\_LIFE\_MEDIUM.

### RWH\_WRITE\_LIFE\_EXTREME

Data written to this inode or via this open file description is expected to have a lifetime longer than data written with RWH\_WRITE\_LIFE\_LONG.

All the write-specific hints are relative to each other, and no individual absolute meaning should be attributed to them.

## RETURN VALUE

For a successful call, the return value depends on the operation:

## F\_DUPFD

The new file descriptor.

## F\_GETFD

Value of file descriptor flags.

## F\_GETFL

Value of file status flags.

## F\_GETLEASE

Type of lease held on file descriptor.

## F\_GETOWN

Value of file descriptor owner.

## F\_GETSIG

Value of signal sent when read or write becomes possible, or zero for traditional SIGIO behavior.

## F\_GETPIPE\_SZ, F\_SETPIPE\_SZ

The pipe capacity.

## F\_GET\_SEALS

A bit mask identifying the seals that have been set for the inode referred to by fd.

## All other commands

Zero.

On error, -1 is returned, and errno is set appropriately.

## ERRORS

### EACCES or EAGAIN

Operation is prohibited by locks held by other processes.

EAGAIN The operation is prohibited because the file has been memory-mapped by another process.

EBADF fd is not an open file descriptor

EBADF cmd is F\_SETLK or F\_SETLKW and the file descriptor open mode doesn't match with the type of lock requested.

EBUSY cmd is F\_SETPIPE\_SZ and the new pipe capacity specified in arg is smaller than the amount of buffer space currently used to store data in the pipe.

EBUSY cmd is F\_ADD\_SEALS, arg includes F\_SEAL\_WRITE, and there exists

a writable, shared mapping on the file referred to by fd.

#### EDEADLK

It was detected that the specified F\_SETLK command would cause a deadlock.

EFAULT lock is outside your accessible address space.

EINTR cmd is F\_SETLK or F\_OFD\_SETLK and the operation was interrupted by a signal; see signal(7).

EINTR cmd is F\_GETLK, F\_SETLK, F\_OFD\_GETLK, or F\_OFD\_SETLK, and the operation was interrupted by a signal before the lock was checked or acquired. Most likely when locking a remote file (e.g., locking over NFS), but can sometimes happen locally.

EINVAL The value specified in cmd is not recognized by this kernel.

EINVAL cmd is F\_ADD\_SEALS and arg includes an unrecognized sealing bit.

EINVAL cmd is F\_ADD\_SEALS or F\_GET\_SEALS and the filesystem containing the inode referred to by fd does not support sealing.

EINVAL cmd is F\_DUPFD and arg is negative or is greater than the maximum allowable value (see the discussion of RLIMIT\_NOFILE in

getrlimit(2)).

EINVAL cmd is F\_SETSIG and arg is not an allowable signal number.

EINVAL cmd is F\_OFD\_SETLK, F\_OFD\_SETLKW, or F\_OFD\_GETLK, and l\_pid was not specified as zero.

EMFILE cmd is F\_DUPFD and the per-process limit on the number of open file descriptors has been reached.

ENOLCK Too many segment locks open, lock table is full, or a remote locking protocol failed (e.g., locking over NFS).

#### ENOTDIR

F\_NOTIFY was specified in cmd, but fd does not refer to a directory.

EPERM cmd is F\_SETPIPE\_SZ and the soft or hard user pipe limit has been reached; see pipe(7).

EPERM Attempted to clear the O\_APPEND flag on a file that has the append-only attribute set.

EPERM cmd was F\_ADD\_SEALS, but fd was not open for writing or the cur?

rent set of seals on the file already includes F\_SEAL\_SEAL.

## CONFORMING TO

SVr4, 4.3BSD, POSIX.1-2001. Only the operations F\_DUPFD, F\_GETFD, F\_SETFD, F\_GETFL, F\_SETFL, F\_GETLK, F\_SETLK, and F\_SETLKW are specified in POSIX.1-2001.

F\_GETOWN and F\_SETOWN are specified in POSIX.1-2001. (To get their definitions, define either \_XOPEN\_SOURCE with the value 500 or greater, or \_POSIX\_C\_SOURCE with the value 200809L or greater.)

F\_DUPFD\_CLOEXEC is specified in POSIX.1-2008. (To get this definition, define \_POSIX\_C\_SOURCE with the value 200809L or greater, or \_XOPEN\_SOURCE with the value 700 or greater.)

F\_GETOWN\_EX, F\_SETOWN\_EX, F\_SETPipe\_SZ, F\_GETPIPE\_SZ, F\_GETSIG, F\_SETSIG, F\_NOTIFY, F\_GETLEASE, and F\_SETLEASE are Linux-specific. (Define the \_GNU\_SOURCE macro to obtain these definitions.)

F\_OFD\_SETLK, F\_OFD\_SETLKW, and F\_OFD\_GETLK are Linux-specific (and one must define \_GNU\_SOURCE to obtain their definitions), but work is being done to have them included in the next version of POSIX.1.

F\_ADD\_SEALS and F\_GET\_SEALS are Linux-specific.

## NOTES

The errors returned by dup2(2) are different from those returned by

F\_DUPFD.

### File locking

The original Linux fcntl() system call was not designed to handle large file offsets (in the flock structure). Consequently, an fcntl64() system call was added in Linux 2.4. The newer system call employs a different structure for file locking, flock64, and corresponding commands, F\_GETLK64, F\_SETLK64, and F\_SETLKW64. However, these details can be ignored by applications using glibc, whose fcntl() wrapper function transparently employs the more recent system call where it is available.

### Record locks

Since kernel 2.0, there is no interaction between the types of lock placed by flock(2) and fcntl().

Several systems have more fields in struct flock such as, for example, `I_sysid` (to identify the machine where the lock is held). Clearly, `I_pid` alone is not going to be very useful if the process holding the lock may live on a different machine; on Linux, while present on some architectures (such as MIPS32), this field is not used.

The original Linux `fcntl()` system call was not designed to handle large file offsets (in the flock structure). Consequently, an `fcntl64()` system call was added in Linux 2.4. The newer system call employs a different structure for file locking, `flock64`, and corresponding commands, `F_GETLK64`, `F_SETLK64`, and `F_SETLKW64`. However, these details can be ignored by applications using glibc, whose `fcntl()` wrapper function transparently employs the more recent system call where it is available.

## Record locking and NFS

Before Linux 3.12, if an NFSv4 client loses contact with the server for a period of time (defined as more than 90 seconds with no communication), it might lose and regain a lock without ever being aware of the fact. (The period of time after which contact is assumed lost is known as the NFSv4 leasetime. On a Linux NFS server, this can be determined by looking at `/proc/fs/nfsd/nfsv4leasetime`, which expresses the period in seconds. The default value for this file is 90.) This scenario potentially risks data corruption, since another process might acquire a lock in the intervening period and perform file I/O.

Since Linux 3.12, if an NFSv4 client loses contact with the server, any I/O to the file by a process which "thinks" it holds a lock will fail until that process closes and reopens the file. A kernel parameter, `nfs.recover_lost_locks`, can be set to 1 to obtain the pre-3.12 behavior, whereby the client will attempt to recover lost locks when contact is reestablished with the server. Because of the attendant risk of data corruption, this parameter defaults to 0 (disabled).

## BUGS

### `F_SETFL`

It is not possible to use `F_SETFL` to change the state of the `O_DSYNC`

and O\_SYNC flags. Attempts to change the state of these flags are silently ignored.

## F\_GETOWN

A limitation of the Linux system call conventions on some architectures (notably i386) means that if a (negative) process group ID to be returned by F\_GETOWN falls in the range -1 to -4095, then the return value is wrongly interpreted by glibc as an error in the system call; that is, the return value of fcntl() will be -1, and errno will contain the (positive) process group ID. The Linux-specific F\_GETOWN\_EX operation avoids this problem. Since glibc version 2.11, glibc makes the kernel F\_GETOWN problem invisible by implementing F\_GETOWN using F\_GETOWN\_EX.

## F\_SETOWN

In Linux 2.4 and earlier, there is a bug that can occur when an unprivileged process uses F\_SETOWN to specify the owner of a socket file descriptor as a process (group) other than the caller. In this case, fcntl() can return -1 with errno set to EPERM, even when the owner process (group) is one that the caller has permission to send signals to. Despite this error return, the file descriptor owner is set, and signals will be sent to the owner.

## Deadlock detection

The deadlock-detection algorithm employed by the kernel when dealing with F\_SETLKW requests can yield both false negatives (failures to detect deadlocks, leaving a set of deadlocked processes blocked indefinitely) and false positives (EDEADLK errors when there is no deadlock).

For example, the kernel limits the lock depth of its dependency search to 10 steps, meaning that circular deadlock chains that exceed that size will not be detected. In addition, the kernel may falsely indicate a deadlock when two or more processes created using the clone(2) CLONE\_FILES flag place locks that appear (to the kernel) to conflict.

## Mandatory locking

The Linux implementation of mandatory locking is subject to race conditions which render it unreliable: a write(2) call that overlaps with a

lock may modify data after the mandatory lock is acquired; a read(2) call that overlaps with a lock may detect changes to data that were made only after a write lock was acquired. Similar races exist between mandatory locks and mmap(2). It is therefore inadvisable to rely on mandatory locking.

## SEE ALSO

dup2(2), flock(2), open(2), socket(2), lockf(3), capabilities(7), feature\_test\_macros(7), lslocks(8)  
locks.txt, mandatory-locking.txt, and dnotify.txt in the Linux kernel source directory Documentation/filesystems/ (on older kernels, these files are directly under the Documentation/ directory, and mandatory-locking.txt is called mandatory.txt)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-12-21

FCNTL(2)