



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'fips\_config.5ossl'***

***\$ man fips\_config.5ossl***

FIPS\_CONFIG(5ossl)                    OpenSSL                    FIPS\_CONFIG(5ossl)

NAME

fips\_config - OpenSSL FIPS configuration

DESCRIPTION

This command is disabled in Red Hat Enterprise Linux. The FIPS provider is automatically loaded when the system is booted in FIPS mode, or when the environment variable OPENSSL\_FORCE\_FIPS\_MODE is set. See the documentation for more information.

Red Hat Enterprise Linux uses a supplementary config for FIPS module located in OpenSSL configuration directory and managed by crypto policies. If present, it should have format

[fips\_sect]

tls1-prf-ems-check = 0

activate = 1

The tls1-prf-ems-check option specifies whether FIPS module will require the presence of extended master secret or not.

The activate option enforces FIPS provider activation.

COPYRIGHT

Copyright 2019-2021 The OpenSSL Project Authors. All Rights Reserved.  
Licensed under the Apache License 2.0 (the "License"). You may not use  
this file except in compliance with the License. You can obtain a copy  
in the file LICENSE in the source distribution or at  
<<https://www.openssl.org/source/license.html>>.

3.0.7                    2023-07-13                    FIPS\_CONFIG(5ossl)