



Rocky Enterprise Linux 9.2 Manual Pages on command 'flatpak-installation.5'

\$ man flatpak-installation.5

FLATPAK INSTALLATION(5) flatpak installation FLATPAK INSTALLATION(5)

NAME

flatpak-installation - Configuration for an installation location

DESCRIPTION

flatpak can operate in system-wide or per-user mode. The system-wide data is located in \$prefix/var/lib/flatpak/, and the per-user data is in \$HOME/.local/share/flatpak/.

In addition to the default installation locations, more system-wide installations can be defined via configuration files /etc/flatpak/installations.d/, which must have the .conf extension and follow the format described below.

FILE FORMAT

The installation config file format is using the same .ini file format that is used for systemd unit files or application .desktop files.

[Installation ...]

All the configuration for the the installation location with name NAME is contained in the [Installation "NAME"] group.

The following keys are recognized:

Path (string)

The path for this installation. This key is mandatory.

DisplayName (string)

The name to use when showing this installation in the UI.

Priority (integer)

A priority for this installation.

StorageType (string)

The type of storage used for this installation. Possible values
include: network, mmc, sdcard, harddisk.

EXAMPLES

[Installation "extra"]

Path=/location/of/sdcard

DisplayName=Extra Installation

StorageType=sdcard

flatpak

FLATPAK INSTALLATION(5)