



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'flatpak-permission-show.1'***

**\$ man flatpak-permission-show.1**

FLATPAK PERMISSION-(1) flatpak permission-show FLATPAK PERMISSION-(1)

### **NAME**

flatpak-permission-show - Show permissions

### **SYNOPSIS**

flatpak permission-show [OPTION...] APP\_ID

### **DESCRIPTION**

Lists dynamic permissions for the given app which are stored in the Flatpak permission store.

When called without arguments, lists all the entries in all permission store tables. When called with one argument, lists all the entries in the named table. When called with two arguments, lists the entry in the named table for the given object ID.

The permission store is used by portals. Each portal generally has its own table in the permission store, and the format of the table entries is specific to each portal.

### **OPTIONS**

The following options are understood:

-h, --help

Show help options and exit.

**-v, --verbose**

Print debug information during command processing.

**--ostree-verbose**

Print OSTree debug information during command processing.

## SEE ALSO

`flatpak(1)`, `flatpak-permissions(1)`, `flatpak-permission-remove(1)`,

`flatpak-permission-reset(1)`, `flatpak-permission-set(1)`

`flatpak`

FLATPAK PERMISSION-(1)